# according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2020/878

Article No.: 396 NEXOL Pflege-Reiniger konz.

Print date: 26.12.2022 Revision date: 10.12.2022 EN Version: 2.0 Issue date: 10.12.2022 Page 1 / 9

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Article No. (manufacturer/supplier) 396

Trade name/designation NEXOL Pflege-Reiniger konz.

1.2. Relevant identified uses of the substance or mixture and uses advised against

### 1.3. Details of the supplier of the safety data sheet

#### supplier (manufacturer/importer/downstream user/distributor)

Knuchel Farben AG

Farben + Lacke Telephone: +41 (0) 32 636 50 40 Steinackerweg 11 Telefax: +41 (0) 32 636 50 45

CH-4537 Wiedlisbach

#### **Department responsible for information:**

laboratory Manager

E-mail (competent person) info@knuchel.ch

1.4. Emergency telephone number

Emergency telephone number 145 (+41 (0)44 251 51 51)

#### **SECTION 2: Hazards identification**

#### 2.1. Classification of the substance or mixture

#### Classification according to Regulation (EC) No 1272/2008 [CLP]

The mixture is classified as not hazardous according to regulation (EC) No 1272/2008 [CLP].

#### 2.2. Label elements

## Labelling according to Regulation (EC) No. 1272/2008 [CLP]

**Hazard pictograms** 

#### **Hazard statements**

not applicable

## **Precautionary statements**

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

#### Hazard components for labelling

not applicable

#### Supplemental hazard information

EUH210 Safety data sheet available on request.

#### 2.3. Other hazards

No information available.

## **SECTION 3: Composition/information on ingredients**

#### 3.2. Mixtures

**Description** polyisocyanate based preparation, containing the following hazardous substances:

Classification according to Regulation (EC) No 1272/2008 [CLP]

EC No.	REACH No.	
CAS No.	Designation	weight-%
Index No.	classification: // Remark	
203-961-6	01-2119475104-44	
112-34-5	2-(2-butoxyethoxy)ethanol	1 - 5
603-096-00-8	Eye Irrit. 2 H319	
423-270-5	01-000016977-53	
164462-16-2	Dicarboxymethylalaninate trisodium salt	1 - 5
	Eye Irrit. 2 H319 / Met. Corr. 1 H290	

#### **Additional information**

Full text of H-phrases: see section 16.

# according to Regulation (EC) No. 1907/2006 (REACH)

according to Regulation (EU) 2020/878

NEXOL Pflege-Reiniger konz. Article No.: 396 Print date: 26.12.2022 Revision date: 10.12.2022

Issue date: 10.12.2022 Page 2 / 9 Version:

#### **SECTION 4: First aid measures**

#### **Description of first aid measures**

#### **General information**

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

#### In case of inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

#### Following skin contact

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

#### After eve contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

#### Following ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

#### Most important symptoms and effects, both acute and delayed

In all cases of doubt, or when symptoms persist, seek medical advice.

#### Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

#### **SECTION 5: Firefighting measures**

#### **Extinguishing media**

#### Suitable extinguishing media

alcohol resistant foam, carbon dioxide, Powder, spray mist, (water)

## Unsuitable extinguishing media

strong water iet

#### Special hazards arising from the substance or mixture

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

#### Advice for firefighters

Provide a conveniently located respiratory protective device. Cool closed containers that are near the source of the fire. Do not allow water used to extinguish fire to enter drains, ground or waterways.

#### **SECTION 6: Accidental release measures**

## Personal precautions, protective equipment and emergency procedures

Ventilate affected area. Do not breathe vapours.

#### **Environmental precautions**

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

#### Methods and material for containment and cleaning up

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13). Clean using cleansing agents. Do not use solvents.

## Reference to other sections

Observe protective provisions (see section 7 and 8).

#### **SECTION 7: Handling and storage**

#### Precautions for safe handling

#### Advices on safe handling

Avoid contact with skin, eyes and clothes. Avoid respiration of swarf. When using do not eat, drink or smoke. Personal protection equipment: refer to section 8. Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

# according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2020/878

Article No.: 396 NEXOL Pflege-Reiniger konz. Print date: 26.12.2022 Revision date: 10.12.2022

 Print date:
 26.12.2022
 Revision date: 10.12.2022
 EN

 Version:
 2.0
 Issue date: 10.12.2022
 Page 3 / 9

#### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

#### Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

#### Further information on storage conditions

Store in a well-ventilated and dry room at temperatures between 15 °C and 30 °C. Keep container tightly closed. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

#### 7.3. Specific end use(s)

Observe technical data sheet. Observe instructions for use.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

#### Occupational exposure limit values:

2-(2-butoxyethoxy)ethanol

Index No. 603-096-00-8 / EC No. 203-961-6 / CAS No. 112-34-5

WEL, TWA: 67.5 mg/m3; 10 ppm WEL, STEL: 101.2 mg/m3; 15 ppm

#### **Additional information**

TWA: Long-term occupational exposure limit value STEL: short-term occupational exposure limit value

Ceiling: peak limitation

#### **DNEL:**

2-(2-butoxyethoxy)ethanol

Index No. 603-096-00-8 / EC No. 203-961-6 / CAS No. 112-34-5

DNEL long-term oral (repeated), Workers: 1,25 mg/kg

DNEL long-term dermal (systemic), Workers: 20 mg/kg bw/day

DNEL acute inhalative (local), Workers: 101,2 mg/m³ DNEL long-term inhalative (local), Workers: 67,5 mg/m³

DNEL long-term inhalative (systemic), Workers: 67,5 mg/m<sup>3</sup>

DNEL long-term dermal (systemic), Consumer: 10 mg/kg bw/day DNEL acute inhalative (local), Consumer: 7,5 mg/m³

DNEL long-term inhalative (local), Consumer: 34 mg/m³ DNEL long-term inhalative (systemic), Consumer: 34 mg/m³

#### PNEC:

#### 2-(2-butoxyethoxy)ethanol

Index No. 603-096-00-8 / EC No. 203-961-6 / CAS No. 112-34-5

PNEC aquatic, freshwater: 1 mg/L PNEC aquatic, marine water: 0,1 mg/L PNEC aquatic, intermittent release: 3,9 mg/L PNEC sediment, freshwater: 4,4 mg/kg PNEC sediment, marine water: 0,44 mg/kg

PNEC, soil: 0,32 mg/kg dw

PNEC sewage treatment plant (STP): 200 mg/L

#### 8.2. Exposure controls

Provide good ventilation. This can be achieved with local or room suction.

#### Personal protection equipment

#### Respiratory protection

Not applicable.

#### Hand protection

For prolonged or repeated handling the following glove material must be used: NBR (Nitrile rubber)

Thickness of the glove material 0.4 mm Breakthrough time: 30 min

Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin: Recommended

## according to Regulation (EC) No. 1907/2006 (REACH)

according to Regulation (EU) 2020/878

Article No.: 396 NEXOL Pflege-Reiniger konz. Print date: 26.12.2022 Revision date: 10.12.2022

Print date: 26.12.2022 Revision date: 10.12.2022 EN Version: 2.0 Revision date: 10.12.2022 Page 4 / 9

glove articles EN ISO 374

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

Eye/face protection

Wear closely fitting protective glasses in case of splashes.

**Body protection** 

Wear suitable protective clothing and gloves.

**Protective measures** 

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

**Environmental exposure controls** 

Do not allow to enter into surface water or drains. See section 7. No additional measures necessary.

#### **SECTION 9: Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

Physical state:

Colour:

Colour:

Characteristic

Codour threshold:

Melting point/freezing point:

Liquid
refer to label
refer to label
not applicable

Initial boiling point and boiling range: 100 °C

Source: PH|EN|501166|GEFBEZ@tr4000

Flammability Combustible liquid.

Lower and upper explosion limit:

Lower explosion limit: 0.9 Vol-% Upper explosion limit: 5.9 Vol-%

Source: 2-(2-butoxyethoxy)ethanol

Flash point: not applicable

Method: DIN 53213

Auto-ignition temperature: 225 °C

Source: 2-(2-butoxyethoxy)ethanol

Decomposition temperature: not applicable pH at 20 °C: not applicable Cinematic viscosity (40°C): < 20 mm²/s

Viscosity at 20 °C: 10 - 12 sec DIN 4 mm

Solubility(ies):

Water solubility at 20 °C: miscible

Partition coefficient: n-octanol/water: see section 12

Vapour pressure at 20 °C: 23 mbar

Source: PH|EN|501166|GEFBEZ@tr4000

Density and/or relative density:

Density at 20 °C: 1.01 g/cm³

Relative vapour density: not applicable particle characteristics: not applicable

9.2. Other information

Solid content: 3 weight-%

solvent content:

Organic solvents: 3 weight-% Water: 95 weight-%

### **SECTION 10: Stability and reactivity**

10.1. Reactivity

## according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2020/878

NEXOL Pflege-Reiniger konz. Article No.: 396 26.12.2022 Revision date: 10.12.2022

Print date: FN Issue date: 10.12.2022 Page 5 / 9 Version:

No information available.

#### 10.2. Chemical stability

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7.

#### 10.3. Possibility of hazardous reactions

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

#### 10.4. Conditions to avoid

Stable when applying the recommended regulations for storage and handling. Further information on correct storage; refer to section 7. Hazardous decomposition byproducts may form with exposure to high temperatures.

#### 10.5. Incompatible materials

not applicable

### 10.6. Hazardous decomposition products

Hazardous decomposition byproducts may form with exposure to high temperatures, e.g.: carbon dioxide, carbon monoxide, smoke, nitrogen oxides.

#### **SECTION 11: Toxicological information**

#### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### **Acute toxicity**

2-(2-butoxyethoxy)ethanol

oral, LD50, Rat: > 200 mg/kg dermal, LD50, Rabbit: 2764 mg/kg

Method: OECD 402 oral, Mouse: 2410 mg/kg Method: OECD 401

inhalative (dust and mist), LC50, Rat: 29 ppm (2 h)

Method: OECD 403

No mortality within the stated exposure time in animal studies. Skin corrosion/irritation; Serious eye damage/eye irritation

## 2-(2-butoxyethoxy)ethanol

Skin (4 h)

Method: OECD 404 No skin irritation eves

Method: OECD 405 Irritating to eyes.

#### Respiratory or skin sensitisation

#### 2-(2-butoxyethoxy)ethanol

Skin, Guinea pig: ; Evaluation not sensitising.

Method: OECD 406 Maximization test; dermal

## CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

#### 2-(2-butoxyethoxy)ethanol

Germ cell mutagenicity; Evaluation Did not show any mutagenic effects in animal experiments.

Tests with bacterial or mammalian cell cultures showed no evidence of mutagenic activity.

Carcinogenicity; Evaluation The chemical structure does not give rise to any particular suspicion of a carcinogenic effect. Reproductive toxicity; Evaluation No effect on fertility in animal studies.

analogy

teratogenicity; Evaluation Did not show any fruit-damaging effect in animal experiments.

#### STOT-single exposure; STOT-repeated exposure

#### 2-(2-butoxyethoxy)ethanol

Specific target organ toxicity (single exposure)

Based on available data, the classification criteria are not met.

Specific target organ toxicity (repeated exposure) Evaluation Based on available data, the classification criteria are not met.

Continued skin contact may cause skin degreasing and dermatitis.

# according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2020/878

Article No.: 396 NEXOL Pflege-Reiniger konz.

 Print date:
 26.12.2022
 Revision date: 10.12.2022
 EN

 Version:
 2.0
 Issue date: 10.12.2022
 Page 6 / 9

#### **Aspiration hazard**

2-(2-butoxyethoxy)ethanol

Aspiration hazard

not applicable

Experiences with human exposure.

Chronic exposure damages the brain and the central nervous system.

#### Practical experience/human evidence

Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are: headache, dizziness, fatigue, amyosthenia, drowsiness, in serious cases: unconsciousness. Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

#### Overall assessment on CMR properties

The ingredients in this mixture do not meet the criteria for classification as CMR category 1A or 1B according to CLP.

#### 11.2. Information on other hazards

#### **Endocrine disrupting properties**

No information available.

#### **SECTION 12: Ecological information**

Classification according to Regulation (EC) No 1272/2008 [CLP]

Do not allow to enter into surface water or drains.

#### 12.1. Toxicity

2-(2-butoxyethoxy)ethanol

Fish toxicity, LC50, Leuciscus idus (golden orfe): > 100 mg/L (96 h)

Static test

Daphnia toxicity, EC50, Daphnia magna: > 100 mg/L (48 h)

Static test; Directive 67/548/EEC, Annex V, C.2; The statement about the toxic effects refers to the norminal concentration

Fish toxicity, LC50, Lepomis macrochirus (Bluegill): 1300 mg/L (96 h)

Method: OECD 203

Static test; The statement about the toxic effects refers to the norminal concentration level.

Algae toxicity, EC50, Scenedesmus subspicatus: > 100 mg/L (96 h)

Method: OECD 201

Static test; The statement about the toxic effects refers to the norminal concentration level.

Bacterial toxicity:, EC10, Activated sludge: > 1995 mg/L (30 min)

Method: OECD 209

The statement about the toxic effects refers to the norminal concentration level.

#### Long-term Ecotoxicity

Toxicological data are not available.

## 12.2. Persistence and degradability

2-(2-butoxyethoxy)ethanol

Persistence and degradability:

No data available

Biodegradation: > 70 % (28 d); Evaluation Readily biodegradable (according to OECD criteria).

Method: OECD 301E

aerobic; activated sludge; 10 mg/l

Biodegradation: > 100 % (28 d); Evaluation Readily biodegradable (according to OECD criteria).

Method: OECD 302B

aerobic; activated sludge; 500 mg/l

Biodegradation:: 80 - 90 %; Evaluation Readily biodegradable (according to OECD criteria).

Method: OECD 301C

aerobic; mixed inoculum; based on: Theoretical oxygen demand

Biodegradation: 76 % (28 d); Evaluation Readily biodegradable (according to OECD criteria).

Method: OECD 301D

Biodegradation: 90 - 100 % (8 d); Evaluation Readily biodegradable (according to OECD criteria).

Method: OECD 302B

## according to Regulation (EC) No. 1907/2006 (REACH)

according to Regulation (EU) 2020/878

Article No.: 396 NEXOL Pflege-Reiniger konz.

 Print date:
 26.12.2022
 Revision date: 10.12.2022
 EN

 Version:
 2.0
 Issue date: 10.12.2022
 Page 7 / 9

Biodegradation: 90 - 100 % (14 d); Evaluation Readily biodegradable (according to OECD criteria).

Method: OECD 301E 12.3. Bioaccumulative potential

2-(2-butoxyethoxy)ethanol

Distribution coefficient n-octanol/water (log KOW): 1

Method: OECD 117

The product has a low bioaccumulation potential

**Bioconcentration factor (BCF)** 

Toxicological data are not available.

12.4. Mobility in soil

2-(2-butoxyethoxy)ethanol

Water: Evaluation The product is water soluble.

Air: Evaluation The substance does not evaporate from the water surface into the atmosphere.

soil: Evaluation A binding to the solid ground phase is not to be expected.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

No information available.

12.7. Other adverse effects

No information available.

## **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

#### Appropriate disposal / Product

Recommendation

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

List of proposed waste codes/waste designations in accordance with EWC

080112 waste paint and varnish other than those mentioned in 08 01 11

Appropriate disposal / Package

Recommendation

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

#### **SECTION 14: Transport information**

This mixture is not classified as dangerous according to international transport regulations (ADR/RID, IMDG, ICAO/IATA).

No dangerous good in sense of this transport regulation.

14.1. UN number or ID number

not applicable

14.2. UN proper shipping name

14.3. Transport hazard class(es)

not applicable

14.4. Packing group

not applicable

14.5. Environmental hazards

Land transport (ADR/RID) not applicable
Marine pollutant not applicable

14.6. Special precautions for user

Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage.

Advices on safe handling: see parts 6 - 8

**Further information** 

# according to Regulation (EC) No. 1907/2006 (REACH)

according to Regulation (EU) 2020/878

NEXOL Pflege-Reiniger konz. Article No.: 396

Print date: 26.12.2022 Revision date: 10.12.2022 Issue date: 10.12.2022 Page 8 / 9 Version:

#### Land transport (ADR/RID)

Tunnel restriction code

Sea transport (IMDG)

EmS-No. not applicable

#### 14.7. Maritime transport in bulk according to IMO instruments

No transport as bulk according IBC - Code.

#### **SECTION 15: Regulatory information**

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### **EU** legislation

#### Directive 2010/75/EU on industrial emissions [Industrial Emissions Directive]

VOC-value (in g/L): 29

#### **National regulations**

#### Restrictions of occupation

Observe employment restrictions under the Maternity Protection Directive 92/85/EEC or stricter national regulations, if

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC) or stricter national regulations, if applicable.

#### 15.2. Chemical Safety Assessment

#### For the following substances of this mixture a chemical safety assessment has been carried out:

EC No. CAS No.	Designation	REACH No.
203-961-6 112-34-5	2-(2-butoxyethoxy)ethanol	01-2119475104-44
423-270-5 164462-16-2	Dicarboxymethylalaninate trisodium salt	01-0000016977-53

## **SECTION 16: Other information**

#### Full text of classification in section 3

Eve Irrit. 2 / H319 Serious eye damage/eye irritation Causes serious eve irritation. Met. Corr. 1 / H290 Corrosive to metals May be corrosive to metals.

#### Abbreviations and acronyms

European Agreement concerning the International Carriage of Dangerous Goods by Road ADR

OEL Occupational Exposure Limit Value

**BLV** Biological Limit Value CAS Chemical Abstracts Service

Classification, Labelling and Packaging CLP **CMR** Carcinogenic, Mutagenic and Reprotoxic

German Institute for Standardization / German industrial standard DIN

**DNEL** Derived No-Effect Level

**EAKV** European Waste Catalogue Directive

Effective Concentration EC EC **European Community** ΕN European Standard

International Air Transport Association – Dangerous Goods Regulations IATA-DGR

International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk IBC Code ICAO-TI International Civil Aviation Organization Technical Instructions for the Safe Transport of Dangerous

Goods by Air

**IMDG** Code International Maritime Code for Dangerous Goods ISO International Organization for Standardization

Lethal Concentration LC

LD Lethal Dose

**MARPOL** Maritime Pollution: The International Convention for the Prevention of Pollution from Ships

**OECD** Organisation for Economic Cooperation and Development

persistent, bioaccumulative, toxic **PBT PNEC** Predicted No Effect Concentration

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals

## according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2020/878

396 26.12.2022 2.0 NEXOL Pflege-Reiniger konz. Article No.: Print date:

Revision date: 10.12.2022 Issue date: 10.12.2022 Page 9 / 9 Version:

RID Regulations concerning the International Carriage of Dangerous Goods by Rail

UN **United Nations** 

Volatile Organic Compounds VOC

very persistent and very bioaccumulative vPvB

#### **Further information**

Classification according to Regulation (EC) No 1272/2008 [CLP]

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in section 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.