Article Print o Versio	date: 27.	12.2022	Leucht-Petrol geruch Revision date: 10.12 Issue date: 10.12.20	2.2022	EN Page 1 / 9
SEC	TION 1: Identif	ication of the	e substance/mixtur	e and of the com	npany/undertaking
1.1.	product identif	iers			
	Article No. (mar Trade name/des			670 Leucht-Petrol gerue VOC-frei	chlos
1.2.	Relevant identi	ified uses of th	ne substance or mixt	ure and uses advis	sed against
1.3.	Relevant identi Coating materia	I to protecting	surfaces safety data sheet		
1.5.			rter/downstream use	r/distributor)	
	Knuchel Farben Farben + Lacke Steinackerweg CH-4537 Wiedli	AG		Telephone: +41 (0) Telefax: +41 (0) 32	
	Department res laboratory Mana E-mail (compete	ager		info@knuchel.ch	
1.4.		ephone numbe		145 (+41 (0)44 251	51 51)
SEC	TION 2: Hazard	ds identificat	ion		
2.1.	Classification of	of the substan	ce or mixture		
	Classification a	according to F	egulation (EC) No 12	272/2008 [CLP]	
	The mixture is c	lassified as ha	zardous according to r	egulation (EC) No 1	1272/2008 [CLP].
	Asp. Tox. 1 / H3 Aquatic Chronic		Aspiration hazard Hazardous to the aqu	uatic environment	May be fatal if swallowed and enters airways. Harmful to aquatic life with long lasting effects.
2.2.	Label elements	-			
	Hazard pictogr		ation (EC) No. 1272/2		
		Danger			
	Hazard stateme				
	H304 H412		fatal if swallowed and to aquatic life with lon		
	Precautionary			ig lasting effects.	
	P101 P102 P103 P273 P301 + P310	If medic Keep ou Read ca Avoid re IF SWA		nstructions. ent.	er or label at hand. ENTER or doctor/physician.
	P331 P405 P501	Keep lo	induce vomiting. cked up. of contents/container	to industrial inciner	ation plant
	Hazard compo	nents for labe	lling		
	Supplemental	-		kanes, iso-alkanes,	cyclic, <2% aromatics
.	Other here and	not appl	cable		
2.3.	Other hazards				
		availabla			

3.2. Mixtures

Description

Article No.: Print date: Version:	e: 27.12.2022 Revision date: 10.12.2022		
		D Regulation (EC) No 1272/2008 [CLP]	
EC No. CAS No. Index No	Desig	CH No. gnation ification // Remark	weight-%
918-481	• • • • •	19457273-39 ocarbons, C10-C13, n-alkanes, iso-alkanes, cyclic, <2% aromatics	80 - 100

	······································	
	Asp. Tox. 1 H304	
271-369-5	01-2119491311-45	
68551-19-9	Alkanes, C12-14-iso-	15 - 25
	Asp. Tox. 1 H304 / Aquatic Chronic 2 H411	
Additional infor	mation	

Full text of classification: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

In case of inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

Following skin contact

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

Following ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

- 4.2. Most important symptoms and effects, both acute and delayed
 - In all cases of doubt, or when symptoms persist, seek medical advice.
- 4.3. Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

alcohol resistant foam, carbon dioxide, Powder, spray mist, (water)

Unsuitable extinguishing media

strong water jet

5.2. Special hazards arising from the substance or mixture

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

5.3. Advice for firefighters

Provide a conveniently located respiratory protective device. Cool closed containers that are near the source of the fire. Do not allow water used to extinguish fire to enter drains, ground or waterways.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Keep away from sources of ignition. Ventilate affected area. Do not breathe vapours.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

6.3. Methods and material for containment and cleaning up

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it

Article No.:	670	Leucht-Petrol geruchlos	
Print date:	27.12.2022	Revision date: 10.12.2022	EN
Version:	8.0	Issue date: 10.12.2022	Page 3 / 9

for disposal in appropriate containers in accordance with the local regulations (see section 13). Clean using cleansing agents. Do not use solvents.

6.4. Reference to other sections

Observe protective provisions (see section 7 and 8).

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advices on safe handling

Avoid formation of flammable and explosive vapour concentrations in the air and exceeding the exposure limit values. Only use the material in places where open light, fire and other flammable sources can be kept away. Electrical equipment must be protected meeting the accepted standard. Product may become electrostatically charged. Provide earthing of containers, equipment, pumps and ventilation facilities. Anti-static clothing including shoes are recommended. Floors must be electrically conductive. Keep away from heat sources, sparks and open flames. Use only spark proof tools. Avoid contact with skin, eyes and clothes. Do not inhale dusts, particulates and spray mist when using this preparation. Avoid respiration of swarf. When using do not eat, drink or smoke. Personal protection equipment: refer to section 8. Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

Further information

Vapours are heavier than air. Vapours form explosive mixtures with air.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks. Soils have to conform to the "Guidelines for avoidance of ignition hazards due to electrostatic charges (TRGS 727)".

Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

Further information on storage conditions

Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 15 °C and 30 °C. Protect from heat and direct sunlight. Keep container tightly closed. Remove all sources of ignition. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

7.3. Specific end use(s)

Observe technical data sheet. Observe instructions for use.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limit values:

not applicable

8.2. Exposure controls

Provide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerosol and solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used.

Personal protection equipment

Respiratory protection

If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory protection must be used. Use only respiratory protection equipment with CE-symbol including four digit test number.

Hand protection

For prolonged or repeated handling the following glove material must be used: NBR (Nitrile rubber)

Thickness of the glove material > 0,4 mm ; Breakthrough time: > 480 min.

Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles EN ISO 374

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

Eye/face protection

Wear closely fitting protective glasses in case of splashes.

Body protection

Article Print o Versio	date:	670 27.12.2022 8.0	Leucht-Petrol geruchlos Revision date: 10.12.2022 EN Issue date: 10.12.2022 Page 4 / 9				
	Wear antis	static clothing of na	ural fibers (cotton) or heat resistant synthetic fibers.				
		e measures act clean skin thoro	ughly with water and soap or use appropriate cleanser.				
		ental exposure co ow to enter into sur	ntrols ace water or drains. See section 7. No additional measures necessary.				
SEC		hysical and cher	-				
9.1.			al and chemical properties				
	Physical s Colour:	state:	Liquid refer to label				
	Odour:		characteristic				
	Odour thr	eshold:	not applicable				
	Melting p	oint/freezing point	not applicable				
	Initial boi	ling point and boil	• •				
			Source: Hydrocarbons, C10-C13, n-alkanes, iso-alkanes, cyclic, <2% aromatics				
	Flammabi	ility:	Combustible liquid.	Combustible liquid.			
		d upper explosion					
		xplosion limit:	0.8 Vol-% 7 Vol-%				
	Upper ex	xplosion limit:	Source: Alkanes, C12-14-iso-				
	Flash point:		65 °C				
			Method: DIN 53213				
	Auto-ignit	tion temperature:	230 °C Source: Alkanes, C12-14-iso-				
	Decompo	sition temperature					
	pH at 20 °		not applicable				
	Cinematio	c viscosity (40°C):	< 20 mm²/s				
	Viscosity	at 20 °C:	11 s 4 mm Method: DIN 53211				
	Solubility Water so	(ies): Iubility at 20 °C:	insoluble				
		coefficient: n-octa	nol/water: see section 12				
	Vapour pi	ressure at 20 °C:	1 mbar Source: Alkanes, C12-14-iso-				
	Density a Density a	nd/or relative dens at 20 °C:	ity: 0.80 g/cm³				
	-	apour density:	not applicable				
		haracteristics:	not applicable				
9.2.	Other info						
	Solid con	tent:	0 weight-%				
	solvent co						
		solvents:	100 weight-% 0 weight-%				

10.1. Reactivity

No information available.

10.2. Chemical stability

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7.

10.3. Possibility of hazardous reactions

Article No.: Print date: Version:		670 27.12.2022 8.0	Leucht-Petrol geruchlos Revision date: 10.12.2022 Issue date: 10.12.2022	EN Page 5 / 9				
	Keep away	/ from strong acids	, strong bases and strong oxidizing ag	jents to avoid exothermic reactions.				
10.4.	Condition Hazardous		products may form with exposure to h	igh temperatures.				
10.5.	Incompati not applica	ble materials ible						
10.6.	Hazardous	s decomposition decomposition by rogen oxides.	high temperatures, e.g.: carbon dioxide,	carbon monoxide,				
SEC	TION 11: 1	oxicological inf	formation					
11.1.	Informatio	on on hazard clas	ses as defined in Regulation (EC) N	o 1272/2008				
	Acute toxicity							
	Hydrocarbons, C10-C13, n-alkanes, iso-alkanes, cyclic, <2% aromatics oral, LD50, Rat: > 15000 mg/kg dermal, LD50, Rabbit: > 3160 mg/kg							
	oral, LD5 dermal, L	Alkanes, C12-14-iso- oral, LD50, Rat: > 5000 mg/kg dermal, LD50, Rabbit: > 2000 mg/kg inhalative (vapours), LC50, Rat 4,6 - 7,64 mg/L (4 h)						
	Skin corro	sion/irritation; Se	erious eye damage/eye irritation					

Hydrocarbons, C10-C13, n-alkanes, iso-alkanes, cyclic, <2% aromatics

Skin (4 h) Based on available data, the classification criteria are not met. eyes

Based on available data, the classification criteria are not met.

Alkanes, C12-14-iso-Skin (4 h) In rare cases the product can cause temporary erythema of the skin. eyes Causes slight eye irritation

Respiratory or skin sensitisation

Hydrocarbons, C10-C13, n-alkanes, iso-alkanes, cyclic, <2% aromatics

Skin: ; Evaluation Based on available data, the classification criteria are not met.

Respiratory system: ; Evaluation Based on available data, the classification criteria are not met.

Alkanes, C12-14-iso-

Skin:

Not to be expected skin or respiratory diseases.

Respiratory system:

An inhalation hazard may only arise if product is used in aerosol conditions or if heated up. If material is misted or if vapors are generated from heating, exposure may cuase irritation of mucous membranes and upper respiratory tract. Based on data from similar materials.

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Hydrocarbons, C10-C13, n-alkanes, iso-alkanes, cyclic, <2% aromatics Germ cell mutagenicity; Evaluation Based on available data, the classification criteria are not met. Carcinogenicity; Evaluation Based on available data, the classification criteria are not met. Reproductive toxicity; Evaluation Based on available data, the classification criteria are not met.

Alkanes, C12-14-iso-Germ cell mutagenicity; Evaluation No mutagenicity Carcinogenicity; Evaluation No cancer production Reproductive toxicity; Evaluation No reproductive toxicity

STOT-single exposure; STOT-repeated exposure

Hydrocarbons, C10-C13, n-alkanes, iso-alkanes, cyclic, <2% aromatics

Specific target organ toxicity (single exposure) Evaluation Based on available data, the classification criteria are not met. Specific target organ toxicity (repeated exposure) Evaluation Based on available data, the classification criteria are not met.

Article No.:	670	Leucht-Petrol geruchlos
Print date:	27.12.2022	Revision date: 10.12.2022
Version:	8.0	Issue date: 10.12.2022

EN Page 6 / 9

Alkanes, C12-14-iso-Specific target organ toxicity (single exposure) No data available Specific target organ toxicity (repeated exposure) No data available

Aspiration hazard

May be fatal if swallowed and enters airways.

Hydrocarbons, C10-C13, n-alkanes, iso-alkanes, cyclic, <2% aromatics Aspiration hazard; Evaluation May be fatal if swallowed and enters airways.

Alkanes, C12-14-iso-

Aspiration hazard May be fatal if swallowed and enters airways.; If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

Practical experience/human evidence

Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are: headache, dizziness, fatigue, amyosthenia, drowsiness, in serious cases: unconsciousness. Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

Overall assessment on CMR properties

The ingredients in this mixture do not meet the criteria for classification as CMR category 1A or 1B according to CLP.

11.2. Information on other hazards

Endocrine disrupting properties

No information available.

SECTION 12: Ecological information

Classification according to Regulation (EC) No 1272/2008 [CLP] Do not allow to enter into surface water or drains.

12.1. Toxicity

Hydrocarbons, C10-C13, n-alkanes, iso-alkanes, cyclic, <2% aromatics Fish toxicity, LC50, Pimephales promelas (fathead minnow): 220 mg/L (96 h) Daphnia toxicity, LC50, crangon crangon: 4,3 mg/L (96 h)

Alkanes, C12-14-iso-Fish toxicity, LL50:: > 750 mg/L

Long-term Ecotoxicity

Harmful to aquatic life with long lasting effects.

12.2. Persistence and degradability

Hydrocarbons, C10-C13, n-alkanes, iso-alkanes, cyclic, <2% aromatics Biodegradation: Evaluation Not readily biodegradable (according to OECD criteria) Alkanes, C12-14-iso-

Biodegradation: Evaluation Not readily biodegradable (according to OECD criteria)

12.3. Bioaccumulative potential

Hydrocarbons, C10-C13, n-alkanes, iso-alkanes, cyclic, <2% aromatics Partition coefficient: n-octanol/water: No further relevant information available.

Alkanes, C12-14-iso-

Distribution coefficient n-octanol/water (log KOW):

This product evaporates.; This product seeps through soils into the groundwater.

12.4. Mobility in soil

Hydrocarbons, C10-C13, n-alkanes, iso-alkanes, cyclic, <2% aromatics soil:

No further relevant information available.

Alkanes, C12-14-iso-

Article N Print dat Version:	te: 27	70 7.12.2022 0	Leucht-Petrol geruchlosRevision date: 10.12.2022ENIssue date: 10.12.2022Page 7 / 9
	soil:		
	No data avail	able	
12.5. R	Results of PB	T and vPvB as	sessment
			do not meet the PBT/vPvB criteria according to REACH, annex XIII.
	Endocrine dis	available.	ties
-	Other adverse No information		
SECTI	ON 13: Disp	osal conside	rations
13.1. V	Vaste treatm	ent methods	
		lisposal / Prod	ict
	Recommenda		
d			ace water or drains. This material and its container must be disposed of in a safe way. Was 2008/98/EC, covering waste and dangerous waste. Dispose of waste according to applicab
			s/waste designations in accordance with EWC
-	40603* Hazardous w		olvents and solvent mixtures Directive 2008/98/EC (waste framework directive).
		lisposal / Pack	
	Recommenda		
N	Non-contamina	ated packages	nay be recycled. Vessels not properly emptied are special waste.
SECTI	ON 14: Trar	sport inform	ition
N	lo dangerous	s good in sens	e of this transport regulation.
14.1. U	JN number o	r ID number	not applicable
14.2. U	JN proper sh	ipping name	
440 T	'un un un un la na		
14.3. I	ransport naz	ard class(es)	not applicable
144 P	Packing grou	n	
17.7. 1	acking grou	P	not applicable
14.5. E	Invironmenta	al hazards	
L	and transport	(ADR/RID)	not applicable
Ν	Aarine polluta	nt	not applicable
14.6. S	Special preca	utions for use	
C	ase of an acc	ays in closed, u ident or leakag fe handling: see	
F	urther inform	nation	
I	and transpo	rt (ADR/RID)	
	unnel restrict		<u>_</u>
	Sea transport		
	EmS-No.		not applicable
		snort in hulk a	cording to IMO instruments
14.7. N		s bulk accordin	-

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture EU legislation Directive 2010/75/EU on industrial emissions [Industrial Emissions Directive]

Article No.: Print date: Version:	670 27.12.2022 8.0	Leucht-Petrol geruchlos Revision date: 10.12.2022 Issue date: 10.12.2022	EN Page 8 / 9	

VOC-value (in g/L): 795

National regulations

Restrictions of occupation

Observe employment restrictions under the Maternity Protection Directive 92/85/EEC or stricter national regulations, if applicable.

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC) or stricter national regulations, if applicable.

15.2. Chemical Safety Assessment

For the following substances of this mixture a chemical safety assessment has been carried out:

EC No. CAS No.	Designation						REACH No.
918-481-9	Hydrocarbons, aromatics	C10-C13,	n-alkanes,	iso-alkanes,	cyclic,	<2%	01-2119457273-39
271-369-5 68551-19-9	Alkanes, C12-14	l-iso-					01-2119491311-45

SECTION 16: Other information

Full text of classificatior	in section 3					
Asp. Tox. 1 / H304	Aspiration hazard	May be fatal if swallowed and enters airways.				
Aquatic Chronic 2 / H411	Hazardous to the aquatic environment	Toxic to aquatic life with long lasting effects.				
Classification procedure						
Classification for mixtures	and used evaluation method according to regula	tion (EC) No 1272/2008 [CLP]				
Asp. Tox. 1	Aspiration hazard	Calculation method.				
Aquatic Chronic 3	Hazardous to the aquatic environment	Calculation method.				
Abbreviations and acror	lyms					
ADR Eur	opean Agreement concerning the International C	arriage of Dangerous Goods by Road				
OEL Oc	cupational Exposure Limit Value					
BLV Bio	logical Limit Value					
CAS Che	emical Abstracts Service					
CLP Cla	ssification, Labelling and Packaging					
CMR Car	cinogenic, Mutagenic and Reprotoxic					
DIN Ge	rman Institute for Standardization / German industrial standard					
DNEL Der	ived No-Effect Level					
EAKV Eur	opean Waste Catalogue Directive					
EC Effe	ective Concentration					
	opean Community					
	opean Standard					
	ernational Air Transport Association – Dangerous					
		ent of Ships carrying Dangerous Chemicals in Bulk				
	ernational Civil Aviation Organization Technical ods by Air	Instructions for the Safe Transport of Dangerous				
	ernational Maritime Code for Dangerous Goods					
	ernational Organization for Standardization					
	hal Concentration					
	hal Dose					
	ritime Pollution: The International Convention for	the Prevention of Pollution from Ships				
	anisation for Economic Cooperation and Develop					
	sistent, bioaccumulative, toxic					
•	dicted No Effect Concentration					
	gistration, Evaluation, Authorisation and Restriction	on of Chemicals				
	gulations concerning the International Carriage of					
	ted Nations					
VOC Vol	atile Organic Compounds					
	y persistent and very bioaccumulative					
	-					

Further information

Classification according to Regulation (EC) No 1272/2008 [CLP]

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in

Article No.:	670	Leucht-Petrol geruchlos		
Print date:	27.12.2022	Revision date: 10.12.2022	EN	
Version:	8.0	Issue date: 10.12.2022	Page 9 / 9	

section 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.