

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2020/878

Article No.: 687  
Print date: 27.12.2022  
Version: 8.0

SILASAN Parkett-Oel  
Revision date: 10.12.2022  
Issue date: 10.12.2022

EN  
Page 1 / 9

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. product identifiers

Article No. (manufacturer/supplier) 687  
Trade name/designation SILASAN Parkett-Oel  
UFI: Y1YU-H5KY-T99Y-2MRP

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Relevant identified uses:

Coating material to protecting surfaces

### 1.3. Details of the supplier of the safety data sheet

#### supplier (manufacturer/importer/downstream user/distributor)

Knuchel Farben AG

Farben + Lacke

Steinackerweg 11

CH-4537 Wiedlisbach

Telephone: +41 (0) 32 636 50 40

Telefax: +41 (0) 32 636 50 45

#### Department responsible for information:

laboratory Manager

E-mail (competent person)

info@knuchel.ch

### 1.4. Emergency telephone number

Emergency telephone number 145 (+41 (0)44 251 51 51)

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

#### Classification according to Regulation (EC) No 1272/2008 [CLP]

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

Flam. Liq. 3 / H226

Flammable liquids

Flammable liquid and vapour.

Aquatic Chronic 3 / H412

Hazardous to the aquatic environment

Harmful to aquatic life with long lasting effects.

### 2.2. Label elements

#### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

#### Hazard pictograms



Warning

#### Hazard statements

H226

Flammable liquid and vapour.

H412

Harmful to aquatic life with long lasting effects.

#### Precautionary statements

P101

If medical advice is needed, have product container or label at hand.

P102

Keep out of reach of children.

P103

Read carefully and follow all instructions.

P210

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233

Keep container tightly closed.

P240

Ground and bond container and receiving equipment.

P241

Use explosion-proof electrical equipment.

P242

Use non-sparking tools.

P243

Take action to prevent static discharges.

P273

Avoid release to the environment.

P280

Wear protective gloves and eye/face protection.

P303 + P361 + P353

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P370 + P378

In case of fire: Use extinguishing powder or sand to extinguish.

P403 + P235

Store in a well-ventilated place. Keep cool.

P501

Dispose of contents/container to industrial incineration plant.

#### Hazard components for labelling

not applicable

#### Supplemental hazard information

not applicable

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2020/878

Article No.: 687  
Print date: 27.12.2022  
Version: 8.0

SILASAN Parkett-Oel  
Revision date: 10.12.2022  
Issue date: 10.12.2022

EN  
Page 2 / 9

## 2.3. Other hazards

No information available.

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

Description Öle

Classification according to Regulation (EC) No 1272/2008 [CLP]

| EC No.<br>CAS No.<br>Index No. | REACH No.<br>Designation<br>classification // Remark   | weight-% |
|--------------------------------|--|----------|
| 918-481-9                      | 01-2119457273-39<br>Hydrocarbons, C10-C13, n-alkanes, iso-alkanes, cyclic, <2% aromatics<br>Asp. Tox. 1 H304 | 40 - 60  |
| 271-369-5<br>68551-19-9        | 01-2119491311-45<br>Alkanes, C12-14-iso-<br>Asp. Tox. 1 H304 / Aquatic Chronic 2 H411                        | 1 - 5    |

#### Additional information

Full text of classification: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### General information

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

#### In case of inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

#### Following skin contact

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

#### After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

#### Following ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

### 4.2. Most important symptoms and effects, both acute and delayed

In all cases of doubt, or when symptoms persist, seek medical advice.

### 4.3. Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

#### Suitable extinguishing media

alcohol resistant foam, carbon dioxide, Powder, spray mist, (water)

#### Unsuitable extinguishing media

strong water jet

### 5.2. Special hazards arising from the substance or mixture

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

### 5.3. Advice for firefighters

Provide a conveniently located respiratory protective device. Cool closed containers that are near the source of the fire. Do not allow water used to extinguish fire to enter drains, ground or waterways.

## SECTION 6: Accidental release measures

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2020/878

Article No.: 687  
Print date: 27.12.2022  
Version: 8.0

SILASAN Parkett-Oel  
Revision date: 10.12.2022  
Issue date: 10.12.2022

EN  
Page 3 / 9

## 6.1. Personal precautions, protective equipment and emergency procedures

Keep away from sources of ignition. Ventilate affected area. Do not breathe vapours.

## 6.2. Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

## 6.3. Methods and material for containment and cleaning up

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13). Clean using cleansing agents. Do not use solvents.

## 6.4. Reference to other sections

Observe protective provisions (see section 7 and 8).

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

#### Advices on safe handling

Avoid formation of flammable and explosive vapour concentrations in the air and exceeding the exposure limit values. Only use the material in places where open light, fire and other flammable sources can be kept away. Electrical equipment must be protected meeting the accepted standard. Product may become electrostatically charged. Provide earthing of containers, equipment, pumps and ventilation facilities. Anti-static clothing including shoes are recommended. Floors must be electrically conductive. Keep away from heat sources, sparks and open flames. Use only spark proof tools. Avoid contact with skin, eyes and clothes. Do not inhale dusts, particulates and spray mist when using this preparation. Avoid respiration of swarf. When using do not eat, drink or smoke. Personal protection equipment: refer to section 8. Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

#### Further information

Vapours are heavier than air. Vapours form explosive mixtures with air.

### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSIVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks. Soils have to conform to the "Guidelines for avoidance of ignition hazards due to electrostatic charges (TRGS 727)".

#### Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

#### Further information on storage conditions

Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 15 °C and 30 °C. Protect from heat and direct sunlight. Keep container tightly closed. Remove all sources of ignition. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

### 7.3. Specific end use(s)

Observe technical data sheet. Observe instructions for use.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Occupational exposure limit values:

not applicable

### 8.2. Exposure controls

Provide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerosol and solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used.

#### Personal protection equipment

##### Respiratory protection

If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory protection must be used. Use only respiratory protection equipment with CE-symbol including four digit test number.

##### Hand protection

For prolonged or repeated handling the following glove material must be used: NBR (Nitrile rubber)

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2020/878

Article No.: 687  
Print date: 27.12.2022  
Version: 8.0

SILASAN Parkett-Oel  
Revision date: 10.12.2022  
Issue date: 10.12.2022

EN  
Page 4 / 9

Thickness of the glove material > 0,4 mm ; Breakthrough time: > 480 min.

Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles EN ISO 374

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

### Eye/face protection

Wear closely fitting protective glasses in case of splashes.

### Body protection

Wear antistatic clothing of natural fibers (cotton) or heat resistant synthetic fibers.

### Protective measures

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

### Environmental exposure controls

Do not allow to enter into surface water or drains. See section 7. No additional measures necessary.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

|   |   |
|---|---|
| <b>Physical state:</b>                          | <b>Liquid</b>   |
| <b>Colour:</b>                                  | <b>refer to label</b>   |
| <b>Odour:</b>                                   | <b>characteristic</b>   |
| <b>Odour threshold:</b>                         | <b>not applicable</b>   |
| <b>Melting point/freezing point:</b>            | <b>not applicable</b>   |
| <b>Initial boiling point and boiling range:</b> | <b>180 °C</b><br>Source: Hydrocarbons, C10-C13, n-alkanes, iso-alkanes, cyclic, <2% aromatics   |
| <b>Flammability:</b>                            | <b>Flammable liquid and vapour.</b>   |
| <b>Lower and upper explosion limit:</b>         |   |
| <b>Lower explosion limit:</b>                   | <b>0.8 Vol-%</b>  |
| <b>Upper explosion limit:</b>                   | <b>7 Vol-%</b><br>Source: Alkanes, C12-14-iso-  |
| <b>Flash point:</b>                             | <b>40 °C</b><br>Method: DIN 53213   |
| <b>Auto-ignition temperature:</b>               | <b>230 °C</b><br>Source: Alkanes, C12-14-iso-   |
| <b>Decomposition temperature:</b>               | <b>not applicable</b>   |
| <b>pH at 20 °C:</b>                             | <b>not applicable</b>   |
| <b>Cinematic viscosity (40°C):</b>              | <b>&lt; 80 mm<sup>2</sup>/s</b>   |
| <b>Viscosity at 20 °C:</b>                      | <b>20 - 24 sec DIN 4 mm</b>   |
| <b>Solubility(ies):</b>                         |   |
| <b>Water solubility at 20 °C:</b>               | <b>insoluble</b>  |
| <b>Partition coefficient: n-octanol/water:</b>  | <b>see section 12</b>   |
| <b>Vapour pressure at 20 °C:</b>                | <b>0.6 mbar</b><br>Source: Hydrocarbons, C10-C13, n-alkanes, iso-alkanes, cyclic, <2% aromatics |
| <b>Density and/or relative density:</b>         |   |
| <b>Density at 20 °C:</b>                        | <b>0.89 g/cm<sup>3</sup></b>  |
| <b>Relative vapour density:</b>                 | <b>not applicable</b>   |
| <b>particle characteristics:</b>                | <b>not applicable</b>   |

### 9.2. Other information

|                          |                    |
|--------------------------|--------------------|
| <b>Solid content:</b>    | <b>55 weight-%</b> |
| <b>solvent content:</b>  |                    |
| <b>Organic solvents:</b> | <b>45 weight-%</b> |
| <b>Water:</b>            | <b>0 weight-%</b>  |

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2020/878

Article No.: 687  
Print date: 27.12.2022  
Version: 8.0

SILASAN Parkett-Oel  
Revision date: 10.12.2022  
Issue date: 10.12.2022

EN  
Page 5 / 9

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No information available.

### 10.2. Chemical stability

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7.

### 10.3. Possibility of hazardous reactions

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

### 10.4. Conditions to avoid

Hazardous decomposition byproducts may form with exposure to high temperatures.

### 10.5. Incompatible materials

not applicable

### 10.6. Hazardous decomposition products

Hazardous decomposition byproducts may form with exposure to high temperatures, e.g.: carbon dioxide, carbon monoxide, smoke, nitrogen oxides.

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

Hydrocarbons, C10-C13, n-alkanes, iso-alkanes, cyclic, <2% aromatics  
oral, LD50, Rat: > 15000 mg/kg  
dermal, LD50, Rabbit: > 3160 mg/kg

Alkanes, C12-14-iso-  
oral, LD50, Rat: > 5000 mg/kg  
dermal, LD50, Rabbit: > 2000 mg/kg  
inhalative (vapours), LC50, Rat 4,6 - 7,64 mg/L (4 h)

#### Skin corrosion/irritation; Serious eye damage/eye irritation

Hydrocarbons, C10-C13, n-alkanes, iso-alkanes, cyclic, <2% aromatics  
Skin (4 h)  
Based on available data, the classification criteria are not met.  
eyes  
Based on available data, the classification criteria are not met.

Alkanes, C12-14-iso-  
Skin (4 h)  
In rare cases the product can cause temporary erythema of the skin.  
eyes  
Causes slight eye irritation

#### Respiratory or skin sensitisation

Hydrocarbons, C10-C13, n-alkanes, iso-alkanes, cyclic, <2% aromatics  
Skin: ; Evaluation Based on available data, the classification criteria are not met.  
Respiratory system: ; Evaluation Based on available data, the classification criteria are not met.

Alkanes, C12-14-iso-  
Skin:  
Not to be expected skin or respiratory diseases.  
Respiratory system:  
An inhalation hazard may only arise if product is used in aerosol conditions or if heated up. If material is misted or if vapors are generated from heating, exposure may cause irritation of mucous membranes and upper respiratory tract. Based on data from similar materials.

#### CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Hydrocarbons, C10-C13, n-alkanes, iso-alkanes, cyclic, <2% aromatics  
Germ cell mutagenicity; Evaluation Based on available data, the classification criteria are not met.  
Carcinogenicity; Evaluation Based on available data, the classification criteria are not met.  
Reproductive toxicity; Evaluation Based on available data, the classification criteria are not met.

Alkanes, C12-14-iso-

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2020/878

Article No.: 687  
Print date: 27.12.2022  
Version: 8.0

SILASAN Parkett-Oel  
Revision date: 10.12.2022  
Issue date: 10.12.2022

EN  
Page 6 / 9

Germ cell mutagenicity; Evaluation No mutagenicity  
Carcinogenicity; Evaluation No cancer production  
Reproductive toxicity; Evaluation No reproductive toxicity

## STOT-single exposure; STOT-repeated exposure

Hydrocarbons, C10-C13, n-alkanes, iso-alkanes, cyclic, <2% aromatics

Specific target organ toxicity (single exposure) Evaluation Based on available data, the classification criteria are not met.  
Specific target organ toxicity (repeated exposure) Evaluation Based on available data, the classification criteria are not met.

Alkanes, C12-14-iso-

Specific target organ toxicity (single exposure)

No data available

Specific target organ toxicity (repeated exposure)

No data available

## Aspiration hazard

Hydrocarbons, C10-C13, n-alkanes, iso-alkanes, cyclic, <2% aromatics

Aspiration hazard; Evaluation May be fatal if swallowed and enters airways.

Alkanes, C12-14-iso-

Aspiration hazard

May be fatal if swallowed and enters airways.; If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

## Practical experience/human evidence

Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are: headache, dizziness, fatigue, amyosthenia, drowsiness, in serious cases: unconsciousness. Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

## Overall assessment on CMR properties

The ingredients in this mixture do not meet the criteria for classification as CMR category 1A or 1B according to CLP.

## 11.2. Information on other hazards

### Endocrine disrupting properties

No information available.

## SECTION 12: Ecological information

Classification according to Regulation (EC) No 1272/2008 [CLP]

Do not allow to enter into surface water or drains.

## 12.1. Toxicity

Hydrocarbons, C10-C13, n-alkanes, iso-alkanes, cyclic, <2% aromatics

Fish toxicity, LC50, Pimephales promelas (fathead minnow): 220 mg/L (96 h)

Daphnia toxicity, LC50, crangon crangon: 4,3 mg/L (96 h)

Alkanes, C12-14-iso-

Fish toxicity, LL50:: > 750 mg/L

### Long-term Ecotoxicity

Harmful to aquatic life with long lasting effects.

## 12.2. Persistence and degradability

Hydrocarbons, C10-C13, n-alkanes, iso-alkanes, cyclic, <2% aromatics

Biodegradation: Evaluation Not readily biodegradable (according to OECD criteria)

Alkanes, C12-14-iso-

Biodegradation: Evaluation Not readily biodegradable (according to OECD criteria)

## 12.3. Bioaccumulative potential

Hydrocarbons, C10-C13, n-alkanes, iso-alkanes, cyclic, <2% aromatics

Partition coefficient: n-octanol/water:

No further relevant information available.

Alkanes, C12-14-iso-

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2020/878

Article No.: 687  
Print date: 27.12.2022  
Version: 8.0

SILASAN Parkett-Oel  
Revision date: 10.12.2022  
Issue date: 10.12.2022

EN  
Page 7 / 9

Distribution coefficient n-octanol/water (log KOW):  
This product evaporates.; This product seeps through soils into the groundwater.

## 12.4. Mobility in soil

Hydrocarbons, C10-C13, n-alkanes, iso-alkanes, cyclic, <2% aromatics  
soil:  
No further relevant information available.

Alkanes, C12-14-iso-  
soil:  
No data available

## 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

## 12.6. Endocrine disrupting properties

No information available.

## 12.7. Other adverse effects

No information available.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

#### Appropriate disposal / Product Recommendation

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste. Dispose of waste according to applicable legislation.

#### List of proposed waste codes/waste designations in accordance with EWC

080111\* Waste paint and varnish containing organic solvents or other dangerous substances

\*Hazardous waste according to Directive 2008/98/EC (waste framework directive).

#### Appropriate disposal / Package Recommendation

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

## SECTION 14: Transport information

### 14.1. UN number or ID number

UN 1263

### 14.2. UN proper shipping name

Land transport (ADR/RID): Paint  
Sea transport (IMDG): PAINT  
Air transport (ICAO-TI / IATA-DGR): Paint

### 14.3. Transport hazard class(es)

3

### 14.4. Packing group

III

### 14.5. Environmental hazards

Land transport (ADR/RID) not applicable  
Marine pollutant not applicable

### 14.6. Special precautions for user

Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage.

Advices on safe handling: see parts 6 - 8

#### Further information

##### Land transport (ADR/RID)

Tunnel restriction code D/E

##### Sea transport (IMDG)

EmS-No. F-E, S-E

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2020/878

Article No.: 687  
Print date: 27.12.2022  
Version: 8.0

SILASAN Parkett-Oel  
Revision date: 10.12.2022  
Issue date: 10.12.2022

EN  
Page 8 / 9

## 14.7. Maritime transport in bulk according to IMO instruments

No transport as bulk according IBC - Code.

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU legislation

##### Directive 2010/75/EU on industrial emissions [Industrial Emissions Directive]

VOC-value (in g/L): 403

#### National regulations

##### Restrictions of occupation

Observe employment restrictions under the Maternity Protection Directive 92/85/EEC or stricter national regulations, if applicable.

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC) or stricter national regulations, if applicable.

### 15.2. Chemical Safety Assessment

For the following substances of this mixture a chemical safety assessment has been carried out:

| EC No.<br>CAS No.       | Designation  | REACH No.        |
|-------------------------|--|------------------|
| 918-481-9               | Hydrocarbons, C10-C13, n-alkanes, iso-alkanes, cyclic, <2% aromatics | 01-2119457273-39 |
| 271-369-5<br>68551-19-9 | Alkanes, C12-14-iso-   | 01-2119491311-45 |

## SECTION 16: Other information

### Full text of classification in section 3

|                          |                                      |  |
|--------------------------|--------------------------------------|--|
| Asp. Tox. 1 / H304       | Aspiration hazard                    | May be fatal if swallowed and enters airways.    |
| Aquatic Chronic 2 / H411 | Hazardous to the aquatic environment | Toxic to aquatic life with long lasting effects. |

### Classification procedure

Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

|                   |                                      |                        |
|-------------------|--------------------------------------|------------------------|
| Flam. Liq. 3      | Flammable liquids                    | On basis of test data. |
| Aquatic Chronic 3 | Hazardous to the aquatic environment | Calculation method.    |

### Abbreviations and acronyms

|           |   |
|-----------|---|
| ADR       | European Agreement concerning the International Carriage of Dangerous Goods by Road                               |
| OEL       | Occupational Exposure Limit Value   |
| BLV       | Biological Limit Value  |
| CAS       | Chemical Abstracts Service  |
| CLP       | Classification, Labelling and Packaging   |
| CMR       | Carcinogenic, Mutagenic and Reprotoxic  |
| DIN       | German Institute for Standardization / German industrial standard   |
| DNEL      | Derived No-Effect Level   |
| EAKV      | European Waste Catalogue Directive  |
| EC        | Effective Concentration   |
| EC        | European Community  |
| EN        | European Standard   |
| IATA-DGR  | International Air Transport Association – Dangerous Goods Regulations   |
| IBC Code  | International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk               |
| ICAO-TI   | International Civil Aviation Organization Technical Instructions for the Safe Transport of Dangerous Goods by Air |
| IMDG Code | International Maritime Code for Dangerous Goods   |
| ISO       | International Organization for Standardization  |
| LC        | Lethal Concentration  |
| LD        | Lethal Dose   |
| MARPOL    | Maritime Pollution: The International Convention for the Prevention of Pollution from Ships                       |
| OECD      | Organisation for Economic Cooperation and Development   |
| PBT       | persistent, bioaccumulative, toxic  |
| PNEC      | Predicted No Effect Concentration   |
| REACH     | Registration, Evaluation, Authorisation and Restriction of Chemicals  |
| RID       | Regulations concerning the International Carriage of Dangerous Goods by Rail                                      |

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2020/878

Article No.: 687  
Print date: 27.12.2022  
Version: 8.0

SILASAN Parkett-Oel  
Revision date: 10.12.2022  
Issue date: 10.12.2022

EN  
Page 9 / 9

---

UN United Nations  
VOC Volatile Organic Compounds  
vPvB very persistent and very bioaccumulative

## Further information

Classification according to Regulation (EC) No 1272/2008 [CLP]

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in section 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.