

Page 1/8

Printing date 16.07.2019 Revision: 16.07.2019 Version number 6

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: Alleskleber transparent

Article number: 1255.8501.51

1.2 Relevant identified uses of the substance or mixture and uses advised against

Sector of Use

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Product category PC1 Adhesives, sealants

Application of the substance / the preparation: Adhesives

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: GYSO AG Kleb- und Dichtungstechnik Steinackerstrasse 34 CH-8302 Kloten

Tel. +41 43 255 55 55 Mail: info@gyso.ch

Further information obtainable from: Technical Department

1.4 Emergency telephone number:

Swiss Toxicological Information Centre: +41 44 251 51 51

UFI 9H00-00VP-J007-U877

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



Flam. Liq. 2 H225 Highly flammable liquid and vapour.



Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms





GHS02

GHS07

Signal word Danger

Hazard-determining components of labelling:

acetone

Hazard statements

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

(Contd. on page 2)



Page 2/8

Printing date 16.07.2019 Revision: 16.07.2019 Version number 6

Trade name: Alleskleber transparent

(Contd. of page 1)

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P240 Ground and bond container and receiving equipment.

P241 Use explosion-proof [electrical/ventilating/lighting] equipment.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Labelling of packages where the contents do not exceed 125 ml

Hazard pictograms





GHS02 GI

GHS07

Signal word Danger

Hazard-determining components of labelling:

acetone

Hazard statements

H336 May cause drowsiness or dizziness.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P271 Use only outdoors or in a well-ventilated area.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 Call a POISON CENTER/doctor if you feel unwell.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3 Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable. vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Chemical characterisation: Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:				
CAS: 67-64-1 EINECS: 200-662-2		♠ Flam. Liq. 2, H225; ♦ Eye Irrit. 2, H319; STOT SE 3, H336	25-50%	
CAS: 64-17-5 EINECS: 200-578-6	ethanol	♠ Flam. Liq. 2, H225	10-25%	

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information: Immediately remove any clothing soiled by the product. After inhalation: Supply fresh air; consult doctor in case of complaints.

(Contd. on page 3)



Printing date 16.07.2019 Revision: 16.07.2019

Version number 6

Page 3/8

Trade name: Alleskleber transparent

(Contd. of page 2)

After skin contact: Immediately rinse with water.

After swallowing: Call for a doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

Symptomatische Behandlung.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

For safety reasons unsuitable extinguishing agents: Water with full jet 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

In case of fire, the following can be released:

5.3 Advice for firefighters

Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

Additional information

Cool endangered receptacles with water spray.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Wear protective equipment. Keep unprotected persons away.

Particular danger of slipping on leaked/spilled product.

6.2 Environmental precautions:

Prevent seepage into sewage system, workpits and cellars.

Do not allow to enter sewers/ surface or ground water.

Prevent from spreading (e.g. by damming-in or oil barriers).

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Dispose of the material collected according to regulations.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling Prevent formation of aerosols.

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles:

Provide solvent resistant, sealed floor.

Store in a cool location.

Store only in the original receptacle.

Information about storage in one common storage facility: Store away from foodstuffs.

(Contd. on page 4)



Page 4/8

Printing date 16.07.2019 Revision: 16.07.2019 Version number 6

Trade name: Alleskleber transparent

(Contd. of page 3)

Further information about storage conditions:

Store in a cool place. +10°C - +25°C.

Protect from frost.

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

Storage class: 3

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

Additional information about design of technical facilities: No further data; see item 7.

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls

Personal protective equipment:

General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

Respiratory protection:

Filter A/P2



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Not necessary if room is well-ventilated.

ABEK Filter

Protection of hands:

Solvent resistant gloves

Protective gloves

Rubber gloves

Only use chemical-protective gloves with CE-labelling of category III.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

Butyl rubber, BR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Nitrile rubber, NBR

Penetration time of glove material

Value for the permeation: Level ≤ 4

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

For the mixture of chemicals mentioned below the penetration time has to be at least 120 minutes (Permeation according to EN 374 Part 3: Level 4).

The determined penetration times according to EN 374 part III are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

(Contd. on page 5)



Page 5/8
Printing date 16.07.2019
Revision: 16.07.2019
Version number 6

Trade name: Alleskleber transparent

(Contd. of page 4)

Eye protection:



Tightly sealed goggles

Body protection: Protective work clothing

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Appearance:

Form: Fluid Colour: Clear

Odour: Characteristic
Odour threshold: Not determined.
pH-value: Not determined.

Change in condition

Melting point/freezing point: Undetermined.

Initial boiling point and boiling range: 55 °C Flash point: -18 °C

Flammability (solid, gas): Not applicable.

Ignition temperature: 425 °C

Decomposition temperature: Not determined.

Auto-ignition temperature: Product is not selfigniting.

Explosive properties: Product is not explosive. However, formation of explosive air/vapour mixtures are

possible.

Explosion limits:

Lower: 2.6 Vol %

Vapour pressure at 20 °C: 233 hPa

Density at 20 °C: 0.9 g/cm³

Relative density Not determined.

Vapour density Not determined.

Evaporation rate Not determined.

Solubility in / Miscibility with

water: Not determined.

Partition coefficient: n-octanol/water: Not determined.

Viscosity:

Dynamic at 20 °C: 1,200 mPas (Brookfield, ISO 2555)

Kinematic: Not determined.

9.2 Other information No further relevant information available.

Volatile Organic Compounds

VOCV (CH) 62.25 %

SECTION 10: Stability and reactivity

10.1 Reactivity No further relevant information available.

10.2 Chemical stability

Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

10.3 Possibility of hazardous reactions Reacts with alcohols, amines, aqueous acids and alkalis.

10.4 Conditions to avoid No further relevant information available.

(Contd. on page 6)



Page 6/8 Printing date 16.07.2019

Revision: 16.07.2019 Version number 6

Trade name: Alleskleber transparent

(Contd. of page 5)

10.5 Incompatible materials: No further relevant information available.

10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:			
67-64-1 acetone			
Oral	LD50	5,800 mg/kg (rat)	
Dermal	LD50	20,000 mg/kg (rbt)	
64-17-5 ethanol			
Oral	LD50	7,060 mg/kg (rat)	
Dermal	LD50	>2,000 mg/kg (rat)	
Inhalative	LC50/4 h	20,000 mg/l (rat)	

Primary irritant effect:

Skin corrosion/irritation Based on available data, the classification criteria are not met.

Serious eye damage/irritation

Causes serious eye irritation.

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness.

STOT-repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity: No further relevant information available.

12.2 Persistence and degradability No further relevant information available.

12.3 Bioaccumulative potential No further relevant information available.

12.4 Mobility in soil No further relevant information available.

Additional ecological information:

General notes: Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

12.5 Results of PBT and vPvB assessment

PBT: Not applicable. vPvB: Not applicable.

12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Must be specially treated adhering to official regulations.

Verordnung des UVEK über Listen zum Verkehr mit Abfällen (SR 814.610.1)

08 04 09 Klebstoff- und Dichtmassenabfälle, die organische Lösungsmittel oder andere gefährliche Stoffe enthalten Klassierung: S = Sonderabfall

(Contd. on page 7)



Page 7/8
Printing date 16.07.2019
Revision: 16.07.2019
Version number 6

Trade name: Alleskleber transparent

(Contd. of page 6)

Uncleaned packaging:

Recommendation:

Dispose of packaging according to regulations on the disposal of packagings.

Dispose of packaging according to regulations on the disposal of packagings.

Recommended cleansing agents: Water, if necessary together with cleansing agents.

SECTION 14: Transport information

14.1 UN-Number

ADR, IMDG, IATA UN1133

14.2 UN proper shipping name

ADR 1133 ADHESIVES IMDG, IATA ADHESIVES

IMDG, IATA



Class 3 Flammable liquids.

Label 3

14.4 Packing group

ADR, IMDG, IATA III

14.5 Environmental hazards:

Marine pollutant:

14.6 Special precautions for userWarning: Flammable liquids.

Danger code (Kemler): 33

EMS Number: F-E,S-E

Stowage Category A

14.7 Transport in bulk according to Annex II of

Marpol and the IBC Code Not applicable.

Transport/Additional information:

ADR

Limited quantities (LQ) 5L

Excepted quantities (EQ) Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

Transport category 3

Tunnel restriction code D/E

IMDG

Limited quantities (LQ) 5L Excepted quantities (EQ) Code: E

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

UN "Model Regulation": UN 1133 ADHESIVES, 3, III

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Labelling according to Regulation (EC) No 1272/2008

Signal word Danger

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

Seveso category P5c FLAMMABLE LIQUIDS

Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t

(Contd. on page 8)



Page 8/8 Printing date 16.07.2019

Revision: 16.07.2019 Version number 6

Trade name: Alleskleber transparent

(Contd. of page 7)

Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t

National regulations:

Technical instructions (air):

Class	Share in %
NK	75.0

Waterhazard class: Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water.

Other regulations, limitations and prohibitive regulations

Substances of very high concern (SVHC) according to REACH, Article 57

None of the ingredients is listed

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

Department issuing SDS: Technical Department

Contact: + 41 (0)43 255 55 55 Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic SVHC: Substances of Very High Concern vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids – Category 2 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

Data compared to the previous version altered.

CH-