



Safety Data Sheet according to (EC) No 1907/2006 as amended

Page 1 of 21

Loctite 2701

SDS No. : 173107
V015.1

Revision: 12.10.2020

printing date: 23.02.2021

Replaces version from: 25.05.2020

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Loctite 2701

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:

Anaerobic Adhesive

1.3. Details of the supplier of the safety data sheet

Henkel Ltd

Wood Lane End

HP2 4RQ Hemel Hempstead

Great Britain

Phone: +44 1442 278000

Fax-no.: +44 1442 278071

ua-productsafety.uk@henkel.com

**Loctite 2701 =
Schraubensicherung 2701**
Festo SE&Co. KG
Ruiter Strasse 82
D-73734 Esslingen
www.Festo.com/en/msds

1.4. Emergency telephone number

24 Hours Emergency Tel: +44 (0)1442 278497

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

Serious eye irritation

Category 2

H319 Causes serious eye irritation.

Skin sensitizer

Category 1

H317 May cause an allergic skin reaction.

Specific target organ toxicity - single exposure

Category 3

H335 May cause respiratory irritation.

Target organ: respiratory tract irritation

Chronic hazards to the aquatic environment

Category 3

H412 Harmful to aquatic life with long lasting effects.

2.2. Label elements

Label elements (CLP):

Hazard pictogram:



Contains

Hydroxypropyl methacrylate

2,2'-Ethylenedioxydiethyl dimethacrylate

Methacryloyloxyethyl succinate
Cumene hydroperoxide
Acetic acid, 2-phenylhydrazide
2-Hydroxyethyl methacrylate

Propylene glycol dimethacrylate

Signal word: Warning

Hazard statement: H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statement: "****" ***For consumer use only: P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children. P501 Dispose of contents/container in accordance with national regulation.***

Precautionary statement: P261 Avoid breathing vapors.
Prevention P280 Wear protective gloves.
P273 Avoid release to the environment.

Precautionary statement: P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
Response P337+P313 If eye irritation persists: Get medical advice/attention.

2.3. Other hazards

Non corrosive to eyes according to test method OECD 438 or based on analogy to similar products tested.

Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

General chemical description:

Anaerobic adhesive

Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No.	EC Number REACH-Reg No.	content	Classification
Hydroxypropyl methacrylate 27813-02-1	248-666-3 01-2119490226-37	25- 50 %	Skin Sens. 1 H317 Eye Irrit. 2 H319
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	203-652-6 01-2119969287-21	5- < 10 %	Skin Sens. 1B H317
Methacryloyloxyethyl succinate 20882-04-6	244-096-4 01-2120137902-58	1- < 3 %	Skin Sens. 1 H317 Eye Dam. 1 H318
Cumene hydroperoxide 80-15-9	201-254-7 01-2119475796-19	1- < 2,5 %	Acute Tox. 4; Dermal H312 STOT RE 2 H373 Acute Tox. 4; Oral H302 Org. Perox. E H242 Acute Tox. 3; Inhalation H331 Aquatic Chronic 2 H411 Skin Corr. 1B H314
methacrylic acid 79-41-4	201-204-4 01-2119463884-26	0,1- < 1 %	Acute Tox. 4; Oral H302 Acute Tox. 3; Dermal H311 Acute Tox. 4; Inhalation H332 Skin Corr. 1A H314 Eye Dam. 1 H318 STOT SE 3 H335
Acetic acid, 2-phenylhydrazide 114-83-0	204-055-3	0,1- < 1 %	Acute Tox. 3; Oral H301 Skin Irrit. 2 H315 Skin Sens. 1 H317 Eye Irrit. 2 H319 STOT SE 3; Inhalation H335 Carc. 2 H351
2-Hydroxyethyl methacrylate 868-77-9	212-782-2 01-2119490169-29	0,1- < 1 %	Skin Irrit. 2 H315 Skin Sens. 1 H317 Eye Irrit. 2 H319
Propylene glycol dimethacrylate 7559-82-2		0,1- < 1 %	STOT SE 3 H335 Skin Sens. 1B H317
1,4-Naphthalenedione 130-15-4	204-977-6	0,01- < 0,1 %	Acute Tox. 3; Oral H301 Skin Irrit. 2; Dermal H315 Skin Sens. 1 H317 Eye Irrit. 2 H319 Acute Tox. 1; Inhalation H330 STOT SE 3; Inhalation H335 Aquatic Acute 1 H400

			Aquatic Chronic 1 H410 M factor (Acute Aquat Tox): 10 M factor (Chron Aquat Tox): 10
--	--	--	---

For full text of the H - statements and other abbreviations see section 16 "Other information".
Substances without classification may have community workplace exposure limits available.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Move to fresh air. If symptoms persist, seek medical advice.

Skin contact:

Rinse with running water and soap.

Obtain medical attention if irritation persists.

Eye contact:

Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.

Ingestion:

Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

EYE: Irritation, conjunctivitis.

RESPIRATORY: Irritation, coughing, shortness of breath, chest tightness.

SKIN: Rash, Urticaria.

4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Carbon dioxide, foam, powder

Extinguishing media which must not be used for safety reasons:

None known

5.2. Special hazards arising from the substance or mixture

In the event of a fire, carbon monoxide (CO), carbon dioxide (CO₂) and nitrogen oxides (NO_x) can be released.

5.3. Advice for firefighters

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

Additional information:

In case of fire, keep containers cool with water spray.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Avoid contact with skin and eyes.

Ensure adequate ventilation.

Wear protective equipment.

6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

6.3. Methods and material for containment and cleaning up

For small spills wipe up with paper towel and place in container for disposal.

For large spills absorb onto inert absorbent material and place in sealed container for disposal.

Dispose of contaminated material as waste according to Section 13.

6.4. Reference to other sections

See advice in section 8

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

Use only in well-ventilated areas.

Avoid skin and eye contact.

Prolonged or repeated skin contact should be avoided

See advice in section 8

Hygiene measures:

Wash hands before work breaks and after finishing work.

Do not eat, drink or smoke while working.

Good industrial hygiene practices should be observed.

7.2. Conditions for safe storage, including any incompatibilities

Refer to Technical Data Sheet

7.3. Specific end use(s)

Anaerobic Adhesive

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Occupational Exposure Limits**

Valid for
Great Britain

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
Methacrylic acid 79-41-4 [METHACRYLIC ACID]	20	72	Time Weighted Average (TWA):		EH40 WEL
Methacrylic acid 79-41-4 [METHACRYLIC ACID]	40	143	Short Term Exposure Limit (STEL):	15 minutes	EH40 WEL

Occupational Exposure Limits

Valid for
Ireland

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
Methacrylic acid 79-41-4 [METHACRYLIC ACID]	20	70	Time Weighted Average (TWA):		IR_OEL
Methacrylic acid 79-41-4 [METHACRYLIC ACID]	40	140	Short Term Exposure Limit (STEL):	15 minutes	IR_OEL

Predicted No-Effect Concentration (PNEC):

Name on list	Environmental Compartment	Exposure period	Value				Remarks
			mg/l	ppm	mg/kg	others	
Methacrylic acid, monoester with propane-1,2-diol 27813-02-1	aqua (freshwater)		0,904 mg/l				
Methacrylic acid, monoester with propane-1,2-diol 27813-02-1	aqua (marine water)		0,904 mg/l				
Methacrylic acid, monoester with propane-1,2-diol 27813-02-1	sewage treatment plant (STP)		10 mg/l				
Methacrylic acid, monoester with propane-1,2-diol 27813-02-1	aqua (intermittent releases)		0,972 mg/l				
Methacrylic acid, monoester with propane-1,2-diol 27813-02-1	sediment (freshwater)				6,28 mg/kg		
Methacrylic acid, monoester with propane-1,2-diol 27813-02-1	sediment (marine water)				6,28 mg/kg		
Methacrylic acid, monoester with propane-1,2-diol 27813-02-1	Soil				0,727 mg/kg		
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	aqua (freshwater)		0,164 mg/l				
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	aqua (marine water)		0,0164 mg/l				
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	sewage treatment plant (STP)		10 mg/l				
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	aqua (intermittent releases)		0,164 mg/l				
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	sediment (freshwater)				1,85 mg/kg		
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	sediment (marine water)				0,185 mg/kg		
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	Soil				0,274 mg/kg		
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	Air						no hazard identified
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	Predator						no potential for bioaccumulation
.alpha.,.alpha.-Dimethylbenzyl hydroperoxide 80-15-9	aqua (freshwater)		0,0031 mg/l				
.alpha.,.alpha.-Dimethylbenzyl hydroperoxide 80-15-9	aqua (marine water)		0,00031 mg/l				
.alpha.,.alpha.-Dimethylbenzyl hydroperoxide 80-15-9	aqua (intermittent releases)		0,031 mg/l				
.alpha.,.alpha.-Dimethylbenzyl hydroperoxide 80-15-9	Sewage treatment plant		0,35 mg/l				
.alpha.,.alpha.-Dimethylbenzyl hydroperoxide 80-15-9	sediment (freshwater)				0,023 mg/kg		
.alpha.,.alpha.-Dimethylbenzyl hydroperoxide 80-15-9	sediment (marine water)				0,0023 mg/kg		
.alpha.,.alpha.-Dimethylbenzyl hydroperoxide 80-15-9	Soil				0,0029 mg/kg		
methacrylic acid 79-41-4	aqua (freshwater)		0,82 mg/l				
methacrylic acid 79-41-4	aqua (marine water)		0,82 mg/l				
methacrylic acid 79-41-4	sewage treatment plant (STP)		10 mg/l				

methacrylic acid 79-41-4	aqua (intermittent releases)		0,82 mg/l				
methacrylic acid 79-41-4	Soil				1,2 mg/kg		
2-Hydroxyethyl methacrylate 868-77-9	aqua (freshwater)		0,482 mg/l				
2-Hydroxyethyl methacrylate 868-77-9	aqua (marine water)		0,482 mg/l				
2-Hydroxyethyl methacrylate 868-77-9	sewage treatment plant (STP)		10 mg/l				
2-Hydroxyethyl methacrylate 868-77-9	aqua (intermittent releases)		1 mg/l				
2-Hydroxyethyl methacrylate 868-77-9	sediment (freshwater)				3,79 mg/kg		
2-Hydroxyethyl methacrylate 868-77-9	sediment (marine water)				3,79 mg/kg		
2-Hydroxyethyl methacrylate 868-77-9	Soil				0,476 mg/kg		
2-Hydroxyethyl methacrylate 868-77-9	Predator						no potential for bioaccumulation

Derived No-Effect Level (DNEL):

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
Methacrylic acid, monoester with propane-1,2-diol 27813-02-1	Workers	dermal	Long term exposure - systemic effects		4,2 mg/kg	
Methacrylic acid, monoester with propane-1,2-diol 27813-02-1	Workers	Inhalation	Long term exposure - systemic effects		14,7 mg/m ³	
Methacrylic acid, monoester with propane-1,2-diol 27813-02-1	General population	dermal	Long term exposure - systemic effects		2,5 mg/kg	
Methacrylic acid, monoester with propane-1,2-diol 27813-02-1	General population	Inhalation	Long term exposure - systemic effects		8,8 mg/m ³	
Methacrylic acid, monoester with propane-1,2-diol 27813-02-1	General population	oral	Long term exposure - systemic effects		2,5 mg/kg	
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	Workers	inhalation	Long term exposure - systemic effects		48,5 mg/m ³	no hazard identified
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	Workers	dermal	Long term exposure - systemic effects		13,9 mg/kg	no hazard identified
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	General population	inhalation	Long term exposure - systemic effects		14,5 mg/m ³	no hazard identified
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	General population	dermal	Long term exposure - systemic effects		8,33 mg/kg	no hazard identified
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	General population	oral	Long term exposure - systemic effects		8,33 mg/kg	no hazard identified
.alpha.,.alpha.-Dimethylbenzyl hydroperoxide 80-15-9	Workers	inhalation	Long term exposure - systemic effects		6 mg/m ³	
methacrylic acid 79-41-4	Workers	Inhalation	Long term exposure - local effects		88 mg/m ³	
methacrylic acid 79-41-4	Workers	Inhalation	Long term exposure - systemic effects		29,6 mg/m ³	
methacrylic acid 79-41-4	Workers	dermal	Long term exposure - systemic effects		4,25 mg/kg	
methacrylic acid 79-41-4	General population	Inhalation	Long term exposure - local effects		6,55 mg/m ³	
methacrylic acid 79-41-4	General population	Inhalation	Long term exposure - systemic effects		6,3 mg/m ³	
methacrylic acid 79-41-4	General population	dermal	Long term exposure - systemic effects		2,55 mg/kg	
2-Hydroxyethyl methacrylate 868-77-9	Workers	dermal	Long term exposure - systemic effects		1,3 mg/kg	no potential for bioaccumulation
2-Hydroxyethyl methacrylate 868-77-9	Workers	Inhalation	Long term exposure - systemic effects		4,9 mg/m ³	no potential for bioaccumulation
2-Hydroxyethyl methacrylate 868-77-9	General population	dermal	Long term exposure - systemic effects		0,83 mg/kg	no potential for bioaccumulation
2-Hydroxyethyl methacrylate 868-77-9	General population	Inhalation	Long term exposure - systemic effects		2,9 mg/m ³	no potential for bioaccumulation
2-Hydroxyethyl methacrylate 868-77-9	General population	oral	Long term exposure - systemic effects		0,83 mg/kg	no potential for bioaccumulation

Biological Exposure Indices:

None

8.2. Exposure controls:

Engineering controls:

Ensure good ventilation/extraction.

Respiratory protection:

Ensure adequate ventilation.

An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area

Filter type: A (EN 14387)

Hand protection:

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):

nitrile rubber (NBR; ≥ 0.4 mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):

nitrile rubber (NBR; ≥ 0.4 mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Safety glasses with sideshields or chemical safety goggles should be worn if there is a risk of splashing.

Protective eye equipment should conform to EN166.

Skin protection:

Wear suitable protective clothing.

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions.

Personal protective equipment should conform to the relevant EN standard.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	liquid green
Odor	mild
Odour threshold	No data available / Not applicable
pH	No data available / Not applicable
Melting point	No data available / Not applicable
Solidification temperature	No data available / Not applicable
Initial boiling point	> 149,0 °C (> 300.2 °F)
Flash point	> 93,00 °C (> 199.4 °F)
Evaporation rate	No data available / Not applicable
Flammability	No data available / Not applicable
Explosive limits	No data available / Not applicable
Vapour pressure	0,3000000 mbar
(20,0 °C (68 °F))	
Relative vapour density:	No data available / Not applicable
Density	1,1 g/cm ³
()	

Bulk density	No data available / Not applicable
Solubility	No data available / Not applicable
Solubility (qualitative) (Solvent: Water)	Partially soluble
Solubility (qualitative) (Solvent: Acetone)	Miscible
Partition coefficient: n-octanol/water	No data available / Not applicable
Auto-ignition temperature	No data available / Not applicable
Decomposition temperature	No data available / Not applicable
Viscosity	No data available / Not applicable
Viscosity (kinematic)	No data available / Not applicable
Explosive properties	No data available / Not applicable
Oxidising properties	No data available / Not applicable

9.2. Other information

No data available / Not applicable

SECTION 10: Stability and reactivity

10.1. Reactivity

Reacts with strong oxidants.

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

See section reactivity

10.4. Conditions to avoid

No decomposition if used according to specifications.

10.5. Incompatible materials

See section reactivity.

10.6. Hazardous decomposition products

carbon oxides.

SECTION 11: Toxicological information

General toxicological information:

Prolonged or repeated contact may cause skin irritation.

11.1. Information on toxicological effects

Acute oral toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Hydroxypropyl methacrylate 27813-02-1	LD50	> 2.000 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	LD50	10.837 mg/kg	rat	not specified
Methacryloyloxyethyl succinate 20882-04-6	LD50	> 2.000 mg/kg	rat	OECD Guideline 423 (Acute Oral toxicity)
Cumene hydroperoxide 80-15-9	LD50	382 mg/kg	rat	other guideline:
methacrylic acid 79-41-4	LD50	1.320 mg/kg	rat	equivalent or similar to OECD Guideline 401 (Acute Oral Toxicity)
Acetic acid, 2-phenylhydrazide 114-83-0	LD50	270 mg/kg	rat	not specified
2-Hydroxyethyl methacrylate 868-77-9	LD50	> 5.000 mg/kg	rat	not specified
Propylene glycol dimethacrylate 7559-82-2	LD50	8.700 mg/kg	rat	FDA Guideline
1,4-Naphthalenedione 130-15-4	LD50	190 mg/kg	rat	not specified

Acute dermal toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Hydroxypropyl methacrylate 27813-02-1	LD50	> 5.000 mg/kg	rabbit	not specified
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	LD50	> 2.000 mg/kg	mouse	not specified
Cumene hydroperoxide 80-15-9	LD50	530 - 1.060 mg/kg	rat	other guideline:
Cumene hydroperoxide 80-15-9	Acute toxicity estimate (ATE)	1.100 mg/kg		Expert judgement
methacrylic acid 79-41-4	LD50	500 - 1.000 mg/kg	rabbit	Dermal Toxicity Screening
methacrylic acid 79-41-4	Acute toxicity estimate (ATE)	500 mg/kg		Expert judgement
2-Hydroxyethyl methacrylate 868-77-9	LD50	> 5.000 mg/kg	rabbit	not specified
Propylene glycol dimethacrylate 7559-82-2	LD50	> 2.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)

Acute inhalative toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Test atmosphere	Exposure time	Species	Method
methacrylic acid 79-41-4	LC50	> 3,6 mg/l	dust/mist	4 h	rat	OECD Guideline 403 (Acute Inhalation Toxicity)
methacrylic acid 79-41-4	Acute toxicity estimate (ATE)	3,61 mg/l				Expert judgement

Skin corrosion/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
Hydroxypropyl methacrylate 27813-02-1	not irritating	24 h	rabbit	Draize Test
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	not irritating	24 h	rabbit	Draize Test
Methacryloyloxyethyl succinate 20882-04-6	not irritating	0,25 h	Human, EPISKIIN™ Reconstituted Human Epidermis model	OECD Guideline 439 (In Vitro Skin Irritation: Reconstructed Human Epidermis (RHE) Test Method)
Methacryloyloxyethyl succinate 20882-04-6	Not Classified	4 h	Human, EPISKIIN™ Reconstituted Human Epidermis model	OECD Guideline 431 (In Vitro Skin Corrosion: Reconstructed Human Epidermis (RHE) Test Method)
Cumene hydroperoxide 80-15-9	corrosive		rabbit	Draize Test
methacrylic acid 79-41-4	corrosive	3 min	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Propylene glycol dimethacrylate 7559-82-2	not irritating	24 h	rabbit	FDA Guideline

Serious eye damage/irritation:

Non corrosive to eyes according to test method OECD 438 or based on analogy to similar products tested.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
Hydroxypropyl methacrylate 27813-02-1	irritating		rabbit	Draize Test
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	not irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Methacryloyloxyethyl succinate 20882-04-6	Category I	10 min	Bovine, cornea, in vitro test	OECD Guideline 437 (BCOP)
methacrylic acid 79-41-4	corrosive		rabbit	Draize Test
2-Hydroxyethyl methacrylate 868-77-9	irritating		rabbit	Draize Test
Propylene glycol dimethacrylate 7559-82-2	not irritating		rabbit	Draize Test

Respiratory or skin sensitization:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Species	Method
Hydroxypropyl methacrylate 27813-02-1	sensitising	Guinea pig maximisation test	guinea pig	not specified
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
methacrylic acid 79-41-4	not sensitising	Buehler test	guinea pig	equivalent or similar to OECD Guideline 406 (Skin Sensitisation)
2-Hydroxyethyl methacrylate 868-77-9	sensitising	Guinea pig maximisation test	guinea pig	not specified
Propylene glycol dimethacrylate 7559-82-2	sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)

Germ cell mutagenicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
Hydroxypropyl methacrylate 27813-02-1	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Hydroxypropyl methacrylate 27813-02-1	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	negative	in vitro mammalian cell micronucleus test	with and without		OECD Guideline 487 (In vitro Mammalian Cell Micronucleus Test)
Methacryloyloxyethyl succinate 20882-04-6	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Cumene hydroperoxide 80-15-9	positive	bacterial reverse mutation assay (e.g Ames test)	without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
methacrylic acid 79-41-4	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		equivalent or similar to OECD Guideline 471 (Bacterial Reverse Mutation Assay)
2-Hydroxyethyl methacrylate 868-77-9	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
2-Hydroxyethyl methacrylate 868-77-9	positive	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
2-Hydroxyethyl methacrylate 868-77-9	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
2-Hydroxyethyl methacrylate 868-77-9	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 472 (Genetic Toxicology: Escherichia coli, Reverse Mutation Assay)

Carcinogenicity

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Sex	Method
Hydroxypropyl methacrylate 27813-02-1	not carcinogenic	inhalation	2 years (102 weeks) 6 hours/day, 5 days/week	rat	male	OECD Guideline 451 (Carcinogenicity Studies)
methacrylic acid 79-41-4	not carcinogenic	inhalation	2 y	mouse	male/female	OECD Guideline 451 (Carcinogenicity Studies)
2-Hydroxyethyl methacrylate 868-77-9		inhalation	102 weeks 6 hours/day, 5 days/week	rat	female	OECD Guideline 451 (Carcinogenicity Studies)

Reproductive toxicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Test type	Route of application	Species	Method
Hydroxypropyl methacrylate 27813-02-1	NOAEL P 400 mg/kg	two- generation study	oral: gavage	rat	OECD Guideline 416 (Two- Generation Reproduction Toxicity Study)
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	NOAEL P 1.000 mg/kg NOAEL F1 1.000 mg/kg		oral: gavage	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
methacrylic acid 79-41-4	NOAEL P 50 mg/kg NOAEL F1 400 mg/kg NOAEL F2 400 mg/kg	Two generation study	oral: gavage	rat	OECD Guideline 416 (Two- Generation Reproduction Toxicity Study)
2-Hydroxyethyl methacrylate 868-77-9	NOAEL P >= 1.000 mg/kg NOAEL F1 >= 1.000 mg/kg	screening	oral: gavage	rat	OECD Combined Repeated Dose and Reproductive / Developmental Toxicity Screening Test (Precursor Protocol of GL 422)

STOT-single exposure:

No data available.

STOT-repeated exposure::

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Route of application	Exposure time / Frequency of treatment	Species	Method
Hydroxypropyl methacrylate 27813-02-1	NOAEL 300 mg/kg	oral: gavage		rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	NOAEL 1.000 mg/kg	oral: gavage	daily	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
Cumene hydroperoxide 80-15-9		inhalation: aerosol	6 h/d 5 d/w	rat	not specified
methacrylic acid 79-41-4		inhalation	90 d 6 h/d, 5 d/w	rat	OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day)
2-Hydroxyethyl methacrylate 868-77-9	NOAEL 100 mg/kg	oral: gavage	once daily	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)

Aspiration hazard:

No data available.

SECTION 12: Ecological information

General ecological information:

Do not empty into drains / surface water / ground water.

12.1. Toxicity

Toxicity (Fish):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Hydroxypropyl methacrylate 27813-02-1	LC50	493 mg/l	48 h	Leuciscus idus melanotus	DIN 38412-15
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	LC50	16,4 mg/l	96 h	Danio rerio	OECD Guideline 203 (Fish, Acute Toxicity Test)
Cumene hydroperoxide 80-15-9	LC50	3,9 mg/l	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
methacrylic acid 79-41-4	LC50	85 mg/l	96 h	Salmo gairdneri (new name: Oncorhynchus mykiss)	EPA OTS 797.1400 (Fish Acute Toxicity Test)
2-Hydroxyethyl methacrylate 868-77-9	LC50	> 100 mg/l	96 h	Oryzias latipes	OECD Guideline 203 (Fish, Acute Toxicity Test)
Propylene glycol dimethacrylate 7559-82-2	LC50	15,95 mg/l	96 h	Danio rerio (reported as Brachydanio rerio)	OECD Guideline 203 (Fish, Acute Toxicity Test)

Toxicity (Daphnia):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Hydroxypropyl methacrylate 27813-02-1	EC50	> 143 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Methacryloyloxyethyl succinate 20882-04-6	EC50	> 515,4 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Cumene hydroperoxide 80-15-9	EC50	18 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
methacrylic acid 79-41-4	EC50	> 130 mg/l	48 h	Daphnia magna	EPA OTS 797.1300 (Aquatic Invertebrate Acute Toxicity Test, Freshwater Daphnids)
2-Hydroxyethyl methacrylate 868-77-9	EC50	380 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Propylene glycol dimethacrylate 7559-82-2	EC50	44,9 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

Chronic toxicity to aquatic invertebrates

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Hydroxypropyl methacrylate 27813-02-1	NOEC	45,2 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	NOEC	32 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
2-Hydroxyethyl methacrylate 868-77-9	NOEC	24,1 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
Propylene glycol dimethacrylate 7559-82-2	NOEC	5,05 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)

Toxicity (Algae):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Hydroxypropyl methacrylate 27813-02-1	EC50	> 97,2 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Hydroxypropyl methacrylate 27813-02-1	NOEC	> 97,2 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	EC50	> 100 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	NOEC	18,6 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Methacryloyloxyethyl succinate 20882-04-6	EC50	> 312 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Methacryloyloxyethyl succinate 20882-04-6	NOEC	21,1 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Cumene hydroperoxide 80-15-9	ErC50	3,1 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
methacrylic acid 79-41-4	NOEC	8,2 mg/l	72 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
methacrylic acid 79-41-4	EC50	45 mg/l	72 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
2-Hydroxyethyl methacrylate 868-77-9	EC50	836 mg/l	72 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
2-Hydroxyethyl methacrylate 868-77-9	NOEC	400 mg/l	72 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Propylene glycol dimethacrylate 7559-82-2	EC50	17,3 mg/l	72 h	Pseudokirchneriella subcapitata (reported as Raphidocelis subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Propylene glycol dimethacrylate 7559-82-2	EC10	6,93 mg/l	72 h	Pseudokirchneriella subcapitata (reported as Raphidocelis subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
1,4-Naphthalenedione 130-15-4	EC50	0,011 mg/l	72 h	Dunaliella bioculata	OECD Guideline 201 (Alga, Growth Inhibition Test)

Toxicity to microorganisms

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Hydroxypropyl methacrylate 27813-02-1	EC10	1.140 mg/l	16 h		not specified
Cumene hydroperoxide 80-15-9	EC10	70 mg/l	30 min		not specified
methacrylic acid 79-41-4	EC10	100 mg/l	17 h		not specified
2-Hydroxyethyl methacrylate 868-77-9	EC0	> 3.000 mg/l	16 h	Pseudomonas fluorescens	other guideline:
Propylene glycol dimethacrylate 7559-82-2	EC50	570 mg/l	3 h	activated sludge of a predominantly domestic sewage	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)

12.2. Persistence and degradability

The product is not biodegradable.

Hazardous substances CAS-No.	Result	Test type	Degradability	Exposure time	Method
Hydroxypropyl methacrylate 27813-02-1	readily biodegradable	aerobic	94,2 %	28 d	OECD Guideline 301 E (Ready biodegradability: Modified OECD Screening Test)
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	readily biodegradable	aerobic	85 %	28 d	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)
Methacryloyloxyethyl succinate 20882-04-6	readily biodegradable, but failing 10-day window	aerobic	80 %	28 d	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
Cumene hydroperoxide 80-15-9		no data	0 %	28 d	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)
methacrylic acid 79-41-4	inherently biodegradable	aerobic	100 %	14 d	OECD Guideline 302 B (Inherent biodegradability: Zahn-Wellens/EMPA Test)
methacrylic acid 79-41-4	readily biodegradable	aerobic	86 %	28 d	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
2-Hydroxyethyl methacrylate 868-77-9	readily biodegradable	aerobic	92 - 100 %	14 d	OECD Guideline 301 C (Ready Biodegradability: Modified MITI Test (I))
Propylene glycol dimethacrylate 7559-82-2	readily biodegradable, but failing 10-day window	aerobic	69 %	28 d	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
1,4-Naphthalenedione 130-15-4	not readily biodegradable.	no data	0 - 60 %		OECD 301 A - F

12.3. Bioaccumulative potential

Hazardous substances CAS-No.	Bioconcentration factor (BCF)	Exposure time	Temperature	Species	Method
Cumene hydroperoxide 80-15-9	9,1			calculation	OECD Guideline 305 (Bioconcentration: Flow-through Fish Test)

12.4. Mobility in soil

Cured adhesives are immobile.

Hazardous substances CAS-No.	LogPow	Temperature	Method
Hydroxypropyl methacrylate 27813-02-1	0,97	20 °C	not specified
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	2,3		OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method)
Methacryloyloxyethyl succinate 20882-04-6	0,783	23 °C	EU Method A.8 (Partition Coefficient)
Cumene hydroperoxide 80-15-9	2,16		not specified
methacrylic acid 79-41-4	0,93	22 °C	OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)
Acetic acid, 2- phenylhydrazide 114-83-0	0,74		not specified
2-Hydroxyethyl methacrylate 868-77-9	0,42	25 °C	OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)
1,4-Naphthalenedione 130-15-4	1,71		not specified

12.5. Results of PBT and vPvB assessment

Hazardous substances CAS-No.	PBT / vPvB
Hydroxypropyl methacrylate 27813-02-1	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Cumene hydroperoxide 80-15-9	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
methacrylic acid 79-41-4	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
2-Hydroxyethyl methacrylate 868-77-9	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
1,4-Naphthalenedione 130-15-4	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

12.6. Other adverse effects

No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product disposal:

Do not empty into drains / surface water / ground water.

Dispose of in accordance with local and national regulations.

Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Disposal must be made according to official regulations.

Waste code

08 04 09* waste adhesives and sealants containing organic solvents and other dangerous substances

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

SECTION 14: Transport information

14.1. UN number

ADR	Not dangerous goods
RID	Not dangerous goods
ADN	Not dangerous goods
IMDG	Not dangerous goods
IATA	Not dangerous goods

14.2. UN proper shipping name

ADR	Not dangerous goods
RID	Not dangerous goods
ADN	Not dangerous goods
IMDG	Not dangerous goods
IATA	Not dangerous goods

14.3. Transport hazard class(es)

ADR	Not dangerous goods
RID	Not dangerous goods
ADN	Not dangerous goods
IMDG	Not dangerous goods
IATA	Not dangerous goods

14.4. Packing group

ADR	Not dangerous goods
RID	Not dangerous goods
ADN	Not dangerous goods
IMDG	Not dangerous goods
IATA	Not dangerous goods

14.5. Environmental hazards

ADR	not applicable
RID	not applicable
ADN	not applicable
IMDG	not applicable
IATA	not applicable

14.6. Special precautions for user

ADR	not applicable
RID	not applicable
ADN	not applicable
IMDG	not applicable
IATA	not applicable

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC content < 3 %
(2010/75/EC)

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

H242 Heating may cause a fire.
H301 Toxic if swallowed.
H302 Harmful if swallowed.
H311 Toxic in contact with skin.
H312 Harmful in contact with skin.
H314 Causes severe skin burns and eye damage.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H330 Fatal if inhaled.
H331 Toxic if inhaled.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.
H351 Suspected of causing cancer.
H373 May cause damage to organs through prolonged or repeated exposure.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.
H411 Toxic to aquatic life with long lasting effects.

Further information:

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (ua-productsafety.de@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Dear Customer,

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your_company.com).

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.