

Safety data sheet
according to ChemV 2015 - SR 813.11

Page 1/9

Printing date 16.07.2020

Revision: 16.07.2020

Version number 5

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: Miranit Record 8020

Article number:

1480

1480.8020.50 (120g)

1.2 Relevant identified uses of the substance or mixture and uses advised against

Sector of Use

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Product category PC1 Adhesives, sealants

Application of the substance / the preparation: Adhesives

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

GYSO AG

Kleb- und Dichtungstechnik

Steinackerstrasse 34

CH-8302 Kloten

Tel. +41 43 255 55 55

Mail: info@gyso.ch

Further information obtainable from: Technical Department

1.4 Emergency telephone number:

Swiss Toxicological Information Centre: +41 44 251 51 51

UFI 9F00-H069-700Q-5WN5

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



Flam. Liq. 2 H225 Highly flammable liquid and vapour.



Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

— CH —

Safety data sheet
according to ChemV 2015 - SR 813.11

Page 2/9

Printing date 16.07.2020

Revision: 16.07.2020

Version number 5

Trade name: Miranit Record 8020

(Contd. of page 1)

Hazard pictograms



GHS02 GHS07 GHS09

Signal word Danger

Hazard-determining components of labelling:

ethyl acetate

acetone

Naphtha (petroleum), hydrotreated light

Hazard statements

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P235 Keep cool.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P280 Wear protective gloves / eye protection / face protection.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Labelling of packages where the contents do not exceed 125 ml

Hazard pictograms



GHS02 GHS07 GHS09

Signal word Danger

Hazard-determining components of labelling:

ethyl acetate

acetone

Naphtha (petroleum), hydrotreated light

Hazard statements

H336 May cause drowsiness or dizziness.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves / eye protection / face protection.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 Call a POISON CENTER/doctor if you feel unwell.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 3)

— CH —

Safety data sheet according to ChemV 2015 - SR 813.11

Page 3/9

Printing date 16.07.2020

Revision: 16.07.2020

Version number 5

Trade name: Miranit Record 8020

(Contd. of page 2)

2.3 Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Chemical characterisation: Mixtures

Description: Chlorbutadiene polymer

Dangerous components:		
CAS: 141-78-6 EINECS: 205-500-4	ethyl acetate ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336	>25-<50%
CAS: 64742-49-0 EC number: 926-605-8	Naphtha (petroleum), hydrotreated light ⚠ Flam. Liq. 2, H225; ⚠ Asp. Tox. 1, H304; ⚠ Aquatic Chronic 2, H411; ⚠ STOT SE 3, H336	>25-<50%
CAS: 67-64-1 EINECS: 200-662-2	acetone ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336	≥5-<10%
CAS: 98-54-4 EINECS: 202-679-0	4-tert-butylphenol ⚠ Repr. 2, H361f; ⚠ Eye Dam. 1, H318; ⚠ Aquatic Chronic 1, H410; ⚠ Skin Irrit. 2, H315	<1.0%

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information: Immediately remove any clothing soiled by the product.

After inhalation: Supply fresh air; consult doctor in case of complaints.

After skin contact: Generally the product does not irritate the skin.

After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing: Call for a doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed Symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents: CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

For safety reasons unsuitable extinguishing agents: Water with full jet

5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

In case of fire, the following can be released:

5.3 Advice for firefighters

Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

Additional information

Cool endangered receptacles with water spray.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Particular danger of slipping on leaked/spilled product.

(Contd. on page 4)

— CH —

Safety data sheet
according to ChemV 2015 - SR 813.11

Page 4/9

Printing date 16.07.2020

Revision: 16.07.2020

Version number 5

Trade name: Miranit Record 8020

(Contd. of page 3)

6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Prevent seepage into sewage system, workpits and cellars.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

Prevent from spreading (e.g. by damming-in or oil barriers).

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Dispose of the material collected according to regulations.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage**7.1 Precautions for safe handling** Prevent formation of aerosols.

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles:

Store in a cool location.

Store only in the original receptacle.

Information about storage in one common storage facility: Not required.

Further information about storage conditions:

Protect from frost.

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

7.3 Specific end use(s) No further relevant information available.**SECTION 8: Exposure controls/personal protection**

Additional information about design of technical facilities: No further data; see item 7.

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

98-54-4 4-tert-butylphenol

MAK (Switzerland)	Short-term value: 1.0 mg/m ³ , 0.16 ppm Long-term value: 0.5 mg/m ³ , 0.08 ppm S B;
-------------------	---

Ingredients with biological limit values:

98-54-4 4-tert-butylphenol

BAT (Switzerland)	2 mg/l Untersuchungsmaterial: Urin Probennahmezeitpunkt: bei Langzeitexposition: Nach mehreren vorangegangenen Schichten, Expositionsende bzw. Schichtende Biol. Parameter: p-ter-Butylphenol
-------------------	---

Additional information: The lists valid during the making were used as basis.

(Contd. on page 5)

CH

Safety data sheet
according to ChemV 2015 - SR 813.11

Page 5/9

Printing date 16.07.2020

Revision: 16.07.2020

Version number 5

Trade name: Miranit Record 8020

(Contd. of page 4)

8.2 Exposure controls

Personal protective equipment:

General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

Respiratory protection:



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Not necessary if room is well-ventilated.

ABEK Filter

Protection of hands:

Neoprene gloves

Protective gloves

Rubber gloves

Empfohlen: Butylkautschuk $\geq 0,5$ mm Schichtdicke. Schutzindex 6, entsprechend > 480 Minuten Permeationszeit nach EN 374.

Only use chemical-protective gloves with CE-labelling of category III.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Nitrile rubber, NBR

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

For the mixture of chemicals mentioned below the penetration time has to be at least 480 minutes (Permeation according to EN 16523-1:2015: Level 6).

The determined penetration times according to EN 16523-1:2015 are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

Eye protection:



Tightly sealed goggles

Body protection: Protective work clothing

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Appearance:

Form:	Fluid
Colour:	Light yellow
Odour:	Solvent-like
Odour threshold:	Not determined.

pH-value: Not determined.

Change in condition

Melting point/freezing point: Undetermined.

Initial boiling point and boiling range: 50-60 °C

(Contd. on page 6)

— CH —

Safety data sheet
according to ChemV 2015 - SR 813.11

Page 6/9

Printing date 16.07.2020

Revision: 16.07.2020

Version number 5

Trade name: Miranit Record 8020

(Contd. of page 5)

Flash point:	-22 °C
Flammability (solid, gas):	Not applicable.
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
Explosion limits:	
Lower:	1.2 Vol %
Vapour pressure at 50 °C:	<1,100 hPa
Density at 20 °C:	0.9 g/cm ³
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with water:	Not miscible or difficult to mix.
Partition coefficient: n-octanol/water:	Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic at 40 °C:	21 mm ² /s
Solvent content:	
Solids content:	27.0 %
9.2 Other information	No further relevant information available.
Volatile Organic Compounds	
VOCV (CH)	72.80 %

SECTION 10: Stability and reactivity

10.1 Reactivity No further relevant information available.

10.2 Chemical stability

Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

10.3 Possibility of hazardous reactions No dangerous reactions known.

10.4 Conditions to avoid No further relevant information available.

10.5 Incompatible materials: No further relevant information available.

10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:

141-78-6 ethyl acetate

Oral	LD50	4,100 mg/kg (mouse)
Dermal	LD50	18,000 mg/kg (rabbit)

67-64-1 acetone

Oral	LD50	9,750 mg/kg (rat)
Dermal	LD50	20,000 mg/kg (rbt)

98-54-4 4-tert-butylphenol

Oral	LD50	2,951 mg/kg (rat)
Dermal	LD50	2,288 mg/kg (rbt)

(Contd. on page 7)

**Safety data sheet
according to ChemV 2015 - SR 813.11**

Page 7/9

Printing date 16.07.2020

Revision: 16.07.2020

Version number 5

Trade name: Miranit Record 8020

(Contd. of page 6)

Primary irritant effect:
Skin corrosion/irritation
Causes skin irritation.
Serious eye damage/irritation
Causes serious eye irritation.
Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)
Germ cell mutagenicity Based on available data, the classification criteria are not met.
Carcinogenicity Based on available data, the classification criteria are not met.
Reproductive toxicity Based on available data, the classification criteria are not met.
STOT-single exposure
May cause drowsiness or dizziness.
STOT-repeated exposure Based on available data, the classification criteria are not met.
Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity: No further relevant information available.

12.2 Persistence and degradability No further relevant information available.

12.3 Bioaccumulative potential No further relevant information available.

12.4 Mobility in soil No further relevant information available.

Ecotoxicological effects:

Remark: Toxic for fish

Additional ecological information:

General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

12.5 Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Must be specially treated adhering to official regulations.

Waste disposal key:

080410 Waste from the manufacture, preparation, distribution and use of adhesives and sealants (including water-repellent materials); Waste adhesives and sealants other than those mentioned in 08 04 09; Classification = S

Uncleaned packaging:

Recommendation: Dispose of packaging according to regulations on the disposal of packagings.

SECTION 14: Transport information

14.1 UN-Number

ADR, IMDG, IATA

UN1133

14.2 UN proper shipping name

ADR

1133 ADHESIVES (vapour pressure at 50°C more than 110 kPa, boiling point of more than 35°C), ENVIRONMENTALLY HAZARDOUS

(Contd. on page 8)

— CH —

Safety data sheet
according to ChemV 2015 - SR 813.11

Page 8/9

Printing date 16.07.2020

Revision: 16.07.2020

Version number 5

Trade name: Miranit Record 8020

(Contd. of page 7)

IMDG

IATA

IMDG



Class

Label

ADHESIVES (Cyclohexane), MARINE POLLUTANT
ADHESIVES

3 Flammable liquids.

3

IATA



Class

Label

14.4 Packing group

ADR, IMDG, IATA

14.5 Environmental hazards:

Marine pollutant:

Special marking (ADR):

14.6 Special precautions for user

Hazard identification number (Kemler code):

EMS Number:

Stowage Category

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

3 Flammable liquids.

3

III

Yes

Symbol (fish and tree)

Symbol (fish and tree)

Warning: Flammable liquids.

33

F-E,S-D

A

Not applicable.

Transport/Additional information:

ADR

Limited quantities (LQ)

Excepted quantities (EQ)

5L

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

Transport category

Tunnel restriction code

3

D/E

IMDG

Limited quantities (LQ)

Excepted quantities (EQ)

5L

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

UN "Model Regulation":

UN 1133 ADHESIVES (VAPOUR PRESSURE AT 50°C MORE THAN 110 KPA, BOILING POINT OF MORE THAN 35°C), 3, II, ENVIRONMENTALLY HAZARDOUS

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Labelling according to Regulation (EC) No 1272/2008

Signal word Danger

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

(Contd. on page 9)

CH —

Safety data sheet
according to ChemV 2015 - SR 813.11

Page 9/9

Printing date 16.07.2020

Revision: 16.07.2020

Version number 5

Trade name: Miranit Record 8020

(Contd. of page 8)

Seveso category

E2 Hazardous to the Aquatic Environment

P5c FLAMMABLE LIQUIDS

Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t

Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t

National regulations:

Technical instructions (air):

Class	Share in %
NK	60.0

Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.

Other regulations, limitations and prohibitive regulations

Substances of very high concern (SVHC) according to REACH, Article 57

None of the ingredients is listed.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H361f Suspected of damaging fertility.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

Department issuing SDS: Technical Department

Contact: + 41 (0)43 255 55 55

Abbreviations and acronyms:

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

SVHC: Substances of Very High Concern

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Repr. 2: Reproductive toxicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

* Data compared to the previous version altered.