



## COOL-FIT 4.0 Übergangs-T90° PE/Messing Mit Innengewinde Rp

### Ausführung:

- Vorisoliertes PE100 SDR11, metrisch
- Messing CuZn40Pb2 mit Innengewinde Rp
- Isolation aus GF HE Schaum
- Schlagfest. Farbe: schwarz
- Elektroschweißfitting mit integrierter Dichtlippe, für eine wasser- und dampfdichte Abdichtung

d (mm)	d/D (mm)	Gewindetyp	Zoll (inch)	DN (mm)	SDR	PN (bar)	Code	Gewicht (kg)
63	63/125	Rp	2	50	11	16	<b>738 953 061</b>	1.700
75	75/140	Rp	2	65	11	16	<b>738 953 062</b>	1.900
90	90/160	Rp	2	80	11	16	<b>738 953 063</b>	2.300
110	110/180	Rp	2	100	11	16	<b>738 953 064</b>	3.100
160	160/250	Rp	2	150	11	16	<b>738 953 067</b>	5.450
225	225/315	Rp	2	200	11	16	<b>738 953 070</b>	18.100
40	40/110	Rp	1	32	11	16	<b>738 953 159</b>	0.500
50	50/110	Rp	1	40	11	16	<b>738 953 160</b>	0.588
63	63/125	Rp	1	50	11	16	<b>738 953 161</b>	0.760
75	75/140	Rp	1	65	11	16	<b>738 953 162</b>	1.246
90	90/160	Rp	1	80	11	16	<b>738 953 163</b>	1.650
110	110/180	Rp	1	100	11	16	<b>738 953 164</b>	2.750
160	160/250	Rp	1	150	11	16	<b>738 953 167</b>	4.450
225	225/315	Rp	1	200	11	16	<b>738 953 170</b>	17.100

d (mm)	L (mm)	L1 (mm)	z (mm)	H (mm)
63	103	48	30	222
75	116	55	36	226
90	130	62	43	241
110	154	72	57	251
160	165	90	330	289
225	185	110	370	446
40	87	40	22	173
50	94	44	25	173
63	103	48	30	186
75	116	55	36	193
90	130	62	43	205
110	154	72	57	215
160	165	90	330	253
225	185	110	370	444

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: [info.ps@georgfischer.com](mailto:info.ps@georgfischer.com)

Internet: <http://www.gfps.com>