




COOL-FIT 2.0F Rohr - Feuerdämmend

Ausführung:

- Vorisoliertes PE100 SDR11, metrisch
- Isolation aus GF HE Schaum
- Mantel schwer entflammbar. Farbe: schwarz
- Mit freien Enden für Elektroschweissung

Anmerkung:

Grössere Dimensionen erhältlich über COOL-FIT 4.0F Sortiment



d/D (mm)	PN (bar)	Code	di (mm)	L (mm)	L1 (mm)
32/75	16	738 174 308	26.2	5000	36
40/90	16	738 174 309	32.6	5000	40
50/90	16	738 174 310	40.8	5000	44
63/110	16	738 174 311	51.4	5000	48
75/125	16	738 174 312	61.4	5000	55
90/140	16	738 174 313	73.6	5000	62
110/160	16	738 174 314	90.0	5000	72
140/200	16	738 174 316	114.6	5000	84

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>