

## SAFETY FOOTWEAR

28.02.2019 PGM-F MA

Product Datasheet uvex 2 xenova 9553.1 - .3 S1 P SRC





## UVEX ARBEITSSCHUTZ GmbH, Würzburger Str. 181-189, D-90766 Fürth

General features	<ul> <li>Low weight and flexible S1 P safety sandal</li> </ul>
	Upper: microvelour
	<ul> <li>Suitable for people allergic to chrome as it's made from</li> </ul>
	synthetic materials
	<ul> <li>All sole materials are free of silicones, plasticisers and</li> </ul>
	other paint wetting impairment substances
	Two adjustable hook-and-loop straps
Protection features	Meets ESD requirements: resistance to ground < 35 megaohm
	100% metal-free uvex xenova® toe cap. Compact
	design, anatomical shape, good lateral stability, no
	thermal conductivity properties
	Metal-free, penetration-resistance insole in accordance
	with the latest standard, which does not impact shoe
	flexibility
	Ergonomically designed outsole made from dual density
	polyurethane with excellent slip resistance
Comfort features	Light weight and optimised shock absorption
	<ul> <li>Outstanding wearer comfort results from a newly</li> </ul>
	developed last and climate-optimised, breathable materials
	Removable comfort insole, antistatic, with moisture
	control system and additional shock absorption in the
	heel and at the front of the foot
	Soft padding on collar
Outsole	PUR outsole, non-marking
	Ergonomically designed tread
	Extremely flexible, excellent shock absorption

Rev. St. 1 Datum: 12.05.2014 Seite 1 von 2

	<ul> <li>Unique PUR outsole system makes the shoe ultra-light</li> <li>Two-layer system with abrasion-resistant and cutresistant outsole</li> <li>Excellent slip resistance</li> <li>Self-cleaning tread</li> <li>Resistant to oil and petrol</li> <li>Resistant to temperatures for short periods up to ca. +120°C</li> </ul>
Certificates	Certified with uvex medicare for individual, orthopaedic inlay soles and individual adjustments of the sole unit such as overall increase, inside and outside increase and other solutions.
Areas of application	Moderate applications
Technical data	Artno. 9553.1 .2 .3 Width 10 11 12 Standard EN ISO 20345:2011 S1 P SRC Size 38 – 52
Accessories	<ul> <li>comfortable climatic insole         (Article-no.: 9534.7-9)     </li> <li>Provides the foot with exceptional, full-surface shock absorption and ensures comfort in high-strain zones</li> <li>Ultra breathable and moisture-absorbing materials</li> <li>Shock absorption zones that assist natural movement</li> <li>Non-irritating, comfortable surface structure</li> </ul>

Rev. St. 1 Datum: 12.05.2014 Seite 2 von 2